# hot handheld laser barcode scanner similar with symbol (OCBS-LA09)

## **Keywords**:

barcode scanner, laser barcode scanner, handheld laser barcode scanner.

#### **Features:**

200scan/sec high scan rate and long reading distance;

Excellent decode capability;

With auto sense and steady stand;

KBW, RS232 and USB supported;

Durable construction combined with future-proofing.

### **Specification:**

Performance Characteristic	S
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic
	Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code
	93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128,
	Chinese code, GS1 DataBar (RSS)series
Scanning Angle	$\pm 65^{\circ}(tilt); \pm 60^{\circ}(pitch); \pm 42^{\circ}(yaw)$
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB for option
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	With
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey or black
User Environment	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)

Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, Class 1

### **Product Details:**

x x x x x x x x