supermarket Omni-directional barcode scanner (Model: OCBS- T006)

Specification:

•	
Operational	
Light Source	650nm visible laser diodes (VLD)
Depth of Scan Field	0 - 206 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1400 scans per second (omni-directional)
Number of Scan Lines	20
Minimum Barcode Width	0.127mm (5mil) @ PCS 90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (blue & red)
Beeper Operation	Programmable tone and volume
System Interfaces	Keyboard wedge, RS-232C, HID USB
Physical	
Dimension	94mmX 158.4mmX 110mm (LxWxH)
Weight	340g (without cable)
Cable Lenth	2M
Tilt	50° forward
Power	
Input Voltage	5VDC ± 10%
Power	1.1 W
Operating Current	220mA @ 5V (Normal):350mA (Max)
Environmental	
Operating Temperature	0degreeC - 50degreeC (32degreeF - 122degreeF)
Storage Temperature	-20 degree C - 60degreeC (-4degreeF- 140degreeF)
Humidity	5% ~ 95% RH, non-condensing
Light Levels	Up to 4000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.0M drops to concrete surface
Regulatory	
Laser Class	CDRH Class IIa; IEC 60825-1: Class I
EMC	CE EN55022 B FCC Part 15 Class B VCCI, BSMI

Product Details:

