

2 USB (OCBP-006)

(OCBP-006)

:

- 1.Support /
- 2.THE
- 3.Automatic
- 4.Temperature
- 5.Modular

:

Resolution	203DPI
Print Speed	20-60mm
Print Size	MAX: 127MM / MIN: 50.8mm
Memory	DRAM: 4M 4
Interface	
Power	
Dimensions	
Weight	
Operating Temperature	
Storage Temperature	
Relative Humidity	
Barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPC+2, UPC+5, UPC-E, UPC-E+2, UPC-E+5, POST, MSI, MSIC, PLESSEY, ITF14, EAN14, QR CODE, DM, PDF417
Font	FONT 0, FONT 8
Resolution & Print Size	(0 ~ 90 ~ 270 ~ 360 ~) 1-10, 360 ~ 270 ~ 90 ~ 0
Supported Languages	PCX, BMP, FLASH, DRAM
Print Size	20MM ~ 60MM
Print Speed	MAX 80MM
Memory	MIN 25MM
Power	
Interface	DC12V 3A
Weight	1.04KG
Dimensions	190 (D) x 135 (137 x (H))
Operating Temperature	5 ~ 45 °C, 20-80% RH
Storage Temperature	-40 ~ 55 °C, ≤93% RH (40 °C)