# 

(□/N:POS-T8)

:0000000

 $4.4.\ 0000000\ 0000\ 00000000\ .1$ 

0000 3.4.0 IPS .00000 0000 0000

 $000\ 00000\ 000000\ 0000000\ .4$ 

00000 0000 000 0000 000 .5 L1 & 000000 L200000 00000 0000 0 0 PIN.

0000000 000000 0000000 000000 000000  $\cdot 7$ 

	$4.4\ \square\square\square\square\square\square$	
	0000000 4 000 ROMO DDR2 512 00000 00 00000000 1/00000000	
	00000 0000 000 SD 0000 00 00000000 32 00000000	
	4.0	
0000000 0000	3 "000000 00000 00000) 15 0000000 000000 0"000000 000000 000	
	4000 000000 000000 00000mAh	
	5 0 0000000 000 AF (00000 000 0.3 000000 000000 0(0000000 000	
	000000 00000 0000 0000 AGPS	
	000000 00000 MSR 0000 ISO7811 7812 00000	
	1 1.8 000 00000 v/3V/5V0 ISO7816 00 000 00000 0000	
	13.56 0000000 ISO/IEC 14443 0000 00/000	
	1 [] [] [] ISO7816	
	two DATA (OOA)	
	WCDMA/GSM	
	WCDMA 2100 [[]]]	
	802.11/	
WPAN		

	5 V-500mA
	USB, RS232
	205
<u> </u>	-20 0000 0000 60 ~ 0000 0000
	-40 0000 000 80 ~ 0000 000
	10% ~ 90 0 0000 000 00000000 00000
<u> </u>	500 [[[
00000000 000000 00000	8 ± 0000KV 15 00000 00000 000000KV ±
	4.4 000000/SP-000000 00000
	SDK

## 

## 

#### 

## :000000

# :00000 00000

#### 

.000 000 0000 00000 00000 000