



Resolution	12x24 / 24x24	
Columns	32 16 / columns	
Dimensions (W x H)	1.5 x 3.0 (mm) (W x H) / 3.0x3.0mm (WXH)	
Dimensions (mm)	58.0 ± 0.1MM x 40.0 mm	
Thickness	0.06 0.08 mm	
Material	PC / ABS	
Interface	USB / RS-232 (optional)	
Memory	256KB	
Power	9V DC / 2A	
Battery	7.4V DC / 1500mAh 5-4 cells. Operating time: 150-120 min.	
Operating Temperature	0°C ~ 50°C	
Storage Temperature	90 ~ -10 : Humidity: 50 ~ 10% (non-condensing)	
Storage Humidity	95 ~ 5% : Humidity: 70 ~ 20% (non-condensing)	
Character Set	30 characters. Supports ASCII.	
Character Set	Supports "1234" digitals. 6 digitals.	
Pin Dimensions	3.5 * 1.1mm	
Options	OCPP-M06-BB	USB + COM + optional.
	OCPP-M06-BB-AI	+ IOS / USB + COM + optional.
	OCPP-M06-B	USB + COM + optional.
	OCPP-M06-U	optional USB + COM + optional.
	OCPP-M06-BB-AA	+ IOS / USB + COM + 1 + optional 7 optional.