

2D 433 **MHz**

(OCBS-W230)

95x65x155mm			
ABS + PC			
160G			
617			
625			
39 ° (H) × 25 ° (V)			
0-360 °			
± 65			
± 60			
25			
1D	UPC / EAN UPC / EAN BooklandEAN ISSN UCC CODE128 GS1-128 ISBT 128 39 39 FullASCII Trioptic 93 32 39 Code11 5 2 5 2 of 5 Codabar MSI 5 2 DataBarvariants GS1 5 3 ISBT CONCAT		
2D	PDF417 MicroPDF417 TLC-39 Maxicode MicroQR		
USB			
100 : M. 300 : M ()			
-10 °C - 45 °C			
-20 °C - 65 °C			
5 -85			
5 -95			
1.8 M			
DC 5V 350MA			
LUMINATION 3.000 : LUX 86000 : .LUX			
EMC EN50081 par1			
FCC EN50082 par1			
IP IP42			
DECODE			
BAR CODE	HD		
39	5.0	5MM	90 mm
100 UPCA	13.0	8MM	200MM
39	20.0	8MM	250MM
PDF 417	6.8	5MM	95MM
	10.0	5MM	110MM
	20.0	10MM	150MM
1 D 39		2.8 0.071) (mm)	
2 D		4.8 0.122) (mm)	