

32 3D 2D 1D 2D 1D USB 2D 1D

Model: OCBS-T009

Product Name	
Laser Wavelength	650NM Red Laser Diode (VLD)
Barcode Resolution	0-200 dpi (UPC / EAN 100 dpi PCS = 90 dpi)
Barcode Height	5 mm Barcode Height
Barcode Width	1800 mm Barcode Width (Barcode) Barcode Width
Barcode Thickness	20
Barcode Material	5mil @ PCS 90
Barcode Length	30 @ UPC / EAN 100
Barcode Type (LED)	Red LED (Barcode Barcode Barcode)
Barcode Interface	Barcode Barcode Barcode
Barcode Protocol	Barcode Barcode Barcode RS-232C HID USB
Barcode Dimensions	
(W H D) mm (mm)	152mm * 110MM * 115 mm
Barcode Weight	815g
Barcode Resolution	2.0 Barcode M Barcode
Barcode Length	50 Barcode Barcode Barcode
Barcode Width	Barcode Barcode
Barcode Power Requirements	
Barcode Voltage	5VDC \pm 10%
Barcode Current	85mA @ 5V (Barcode)
Barcode Power	1.35 W
Barcode Compliance	CDRH Barcode Barcode Barcode. IEC 60825-1: Barcode Barcode Barcode
EMC	CE EN55022 B FCC Barcode Barcode Barcode 15 Barcode VCCI Barcode BSMI
Barcode Environmental	
Barcode Operating Temp	0 °C - 40 °C (32 °F - 104 °F)
Barcode Storage Temp	-20 °C - 60 °C (-4 °C - 140 °F)
Barcode Humidity	5% ~ 90% RH (Barcode Barcode Barcode)
Barcode Shock	1.0 Barcode Barcode Barcode M
Barcode Vibration	Barcode) Barcode 4000 Barcode Barcode)