

433 2 00000000 0000 0000000 000000 000000000 000000000 0000 00000d 0000000 0000000 0000000000

| | |
|------------------------|--|
| Aiming Light Source | 617 nm LED |
| Lighting Light Source | 625 nm LED |
| Scanning Angle | 39° (H) x 25° (V) |
| Rotation Angle | 0 - 360° |
| Elevation Angle | ± 65° |
| Tilt Angle | ± 60° |
| Print Contrast | Higher than 25% |
| 1D | UPC/EAN, UPC/EAN with <u>supplementals</u> , <u>BooklandEAN</u> , ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, <u>Trioptic Code 39</u> , Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, <u>Codabar</u> , MSI, Chinese 2 of 5, GS1 Data <u>Barvariants</u> , Korean 3 of 5, ISBT <u>Concat</u> |
| 2D | PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, <u>Maxicode</u> , QR Code, <u>MicroQR</u> , Aztec |
| Interface | USB (<u>Wireless receiver cable</u>) |
| Communication distance | 433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max) |
| Operating Temperature | -10 deg C - 45 deg C |
| Storage Temperature | -20 deg C - 65 deg C |
| Operating Humidity | 5%-85% |
| Storage Humidity | 5%-95% |
| Durability | Withstands multiple 1.5m drops to concrete |
| Input Power | DC 5V, 280mA |
| Charging time | 6h |