### 

### 

- 2.Bluetooth  $\square$  USB  $\square$  RS232 . $\square$

### 

| 105 × 75 × 45mm ∏   |
|---|
| 134g  |
|   |
| 48MM  |
|   |
| ESC / POS 000000 000000 000000  |
| 90  |
| 8 203)       /  |
| 12x24 / 24x24   |
| 32 16 /columns  |
| 1.5 × 3.0 □□□□□) □□ × H) / 3.0x3.0mm (WXH)                            |
| 58.0 ± 0.1MM 40.0 × □□□mm   |
| 0.06 0.08          mm   |
|   |
| USB[] RS-232[] [][[][[][][][][][][][][][][][][][][]                   |
| 256KB   |
| 9V DC / 2A  |
| 7.4V DC / 1500MA. 0000 00000 00000 5-4 0000 000 00 000000 0000        |
|   |
| 90 ~ [10 : []]][] [] °C 50 ~ °C 10- : []]][][]                        |
| 95 ~ [5 : [] [] [] [] [] [] [] [] [] [] [] [] []                      |
| 0000 30 0000 00 00 0000000 00000000 000000                            |
| 6 000 00 .0000 0000 00 0000 0"1234" 0000000 000 0000000 000 digitals. |
| 3.5 * 1.1mm   |
|   |

### 



### Picture





### Small Size, BIG Performance





Bluetooth, USB and RS232 communication for option;





Low power consumption and large capacity Lithium battery;











### Parameter

| Overall Dimension (W×D×H) | 105×75×45mm   |
|---------------------------|---|
| Weight                    | 134g  |
| Color Million             | Black   |
| Effective print width     | 48mm 34.0   |
| Print method              | Thermal line printing   |
| Print commands            | ESC/POS compatible command set  |
| Printspeed                | Up to 90mm/sec  |
| Resolution                | 8 dots/mm(203dpi)   |
| Printfont                 | 12x24/24x24   |
| Column capacity           | 32 columns/ 16columns   |
| Character size            | 1.5 x 3.0 mm(W x H)/3.0x3.0mm(WxH)  |
| Paper dimensions (0)      | 58.0±0.1mm x diameter 40.0mm  |
| Paper thickness           | 0.06 to 0.08mm  |
| Characterset              | Alphanumeric/ Chinese Kanji   |
| Interface                 | USB, RS-232 Bluetooth (optional)  |
| Flash                     | 256KB   |
| Power Adapter             | 9VDC/2A   |
| Battery Power             | 7.4V DC/ 1500mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features            | Paper detection, power detection, Manual shut down  |

| Working conditions   | Temperature:-10°C~50°C,Humidity:10%~90%                                       |    |
|----------------------|---|----|
| Storage conditions   | itions Temperature:-20°C~70°C,Humidity:5%~95%                                 |    |
| Device name          | Can be customized, letter and digital for option, at max 30 ASCII characters. | 01 |
| Password             | Enter default pairing code "1234", it can be customized. At max 6 digitals.   |    |
| Power plug dimension | 3.5*1.1mm   |    |

### Applications

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

















Illegal Parking Ticket

Drugstore

Price Tag

Retail / Farm









# Production Line



Capacity

| · 100    |                                 | 200                      | 100                                  |
|----------|---------------------------------|--------------------------|--------------------------------------|
| Verified | Product Name                    | Production Line Capacity | Actual Units Produced(Previous Year) |
| ~        | Thermal Printer                 | 40,000 Sets / Month      | 250,000 Sets                         |
| 1        | Dot Matrix Printer              | 15,000 Sets / Month      | 10,000 Sets                          |
| 1        | Bluetooth Printer               | 30,000 Sets / Month      | 20,000 Sets                          |
| V        | Barcode Scanner                 | 40,000 Sets / Month      | 20,000 Sets                          |
| 1        | POS Machine                     | 5,000 Sets / Month       | 10,000 Sets                          |
| 1        | Magnetic Card Reader and Writer | 45,000 Sets / Month      | 50,000 Sets                          |
|          |                                 |                          |                                      |

√ Indicates information has been verifed onsite by TUV on 2013.7.15

# Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

### **Test Equipments**

| Verified | Machine Name             | Brand & Model No. | Quantity |           |
|----------|--------------------------|-------------------|----------|-----------|
| 1        | Ageing Tester            | No information    | 6        |           |
| 4        | Withstand Voltage Tester | CC2670A           | 1        |           |
| 1        | Oscilloscope             | TBS1102           | 1        | 1.00      |
| 1        | DC Power Supply          | PS-305DM          | 6        | 24571     |
| 1 .00    | Digital Torque Meter     | HP100             | 1        | www.ocomi |
| Maria    | Calliper                 | GUANGLU           | 2        | " NAN SI  |
| ~        | Multi-meter              | VC890D            | 7        | - Ar      |
| ~        | Test Computer            | No Information    | 13       |           |
|          |                          |                   |          |           |

✓ Indicates information has been verifed onsite by TUV on 2013.7.15

# Certifications



# Packing and Shipment



































### Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.











## Why you choose us?





### Company Profile

### This Assessed Supplier Has Been **Independently Verified**

Build Your Growth On Trust









OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control; production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years " experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



### Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: 11/F, Tower A, New Energy Building, #2009, Nanhai Ave., Nanshan district, Shenzhen

Guangdong, 518054, China;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

www.ocominc.com Trademanager: szocominc, cn1500439666;

QQ: 2485890637.190852203; Tel/Fax: +86.755.8605.3207. WWW.ocol

