رمز الماسح qr المحمول pos الباركود OEM 2D المحمولة قارئ جواز السفر OCBS -2015 الضوئي

الميزات:

عالية الأداء فك التشفير
مع استشعار الأشعة تحت الحمراء للكشف عن تتحرك الباركود
أنسنة الإضاءة و أمبير ؛ تصميم التركيز
وظيفة قوية لتحرير البيانات
التصميم الهيكلي الموثوق ودائم
تصميم منخفض الطاقة متوافق مع جميع أنواع الأجهزة

تخصيص

Feature :

- **High Performance Decoding**
  Can read up to 3mil barcodes, DPM barcodes on spare parts, OCR barcodes and can take picture.

- **With IR Sensor to Detect Moving Barcode**
  IR function can detect upto 40cm moving barcode,and decoding within 100ms

- **Humanized Lighting & Focus Design**
  The soft illumination without flash frequency and a clear/accurate cross laser focusing system not only produce visual fatigue in continuous high-strength operating conditions, but also greatly improve the efficiency of operation.

- **Strong Data Editing Function**
  Some functions can be set on scanners before sending data to host machine. It help to input data as a requested way to achieve the goal of editing data flexible.

- **Reliable and Durable Structural Design**
  Can withstand repeated drops from a height of 1.8 meters, IP42 protection level.

- **Low Power Design Compatible with All Types of Devices**
  Low power design can help to solve the connection problems which caused by insufficient USB drive capacity on the host computer or excessive voltage requirements for the access device etc. It help to maximize the compatibility of the device.

Scan	Sensor	CMOS	Accuracy*	≥3mil
	Resolution	1280 × 960	Movement Tolerance*	2 m/s
	Light	White LED/Red LED	Field of view angle	Horizontal40.5°, Vertical30.4°
	Focus	Laser 650nm	Symbolic contrast*	≥25%
	Barcodes	2D	PDF417, QR Code, Data Matrix, Chinese Sensible Code(汉信码), etc.	
		1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5,Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey, etc.	

Reading Depth*	Barcode Type	2015-1	2015-2
	EAN-13（13mil）	25mm~155mm	40mm~410mm
	Code 39（5mil）	50mm~100mm	110mm~250mm
	PDF 417（6.7mil）	40mm~105mm	115mm~190mm
	Data Matrix（10mil）	40mm~110mm	100mm~250mm
	QR Code （15mil）	35mm~155mm	70mm~280mm
Barcode Sensitivity*	Pitch	±50°	
	Tilt	360°	
	Skew	±50°	

Electrical	Interface	RS-232,USB,PS/2	Prompt method	Buzzer, LED indication, vibrator
	Dimension(mm)	166(W)×107(D)×71 (H)	Voltage	5 VDC±5%
	Weight	208g	Rated power consumption	1251 mW(Typical values)
	Current@5 VDC	Operating current 266 mA（Typical values）	Standby current	109 mA
Environmental	Working Temperature	-20℃~50℃	Electrostatic	±16 kV (Air discharge), ±8 kV (direct discharge)
	Storage Temperature	-40℃~+70℃	Anti Drop	1.8m
	Humidity	5%~95%（Non-condensing）	IP Grade	IP42
Certificates		FCC Part15 Class B, CE EMC Class B		
Accessories	cable	USB	USBcable, for connection and transmission	
		RS-232	RS-232cable(optional), for connection and transmission	
		PS/2	PS/2cable(optional), for connection and transmission	
	adapter		5Vadapter(optional), forRS232 power supply. Out put: DC 5V, 1.5A. Input: AC 100~240V, 50~60Hz	
Others	Intelligent Induction Stand		Optional	
	Data Editing		Supported	