

(OCBS-D5000)

OCBS-D5000

OCBS-D5000

- 5.1.1 OCBS-D5000
- 1GB 8 GB
- 1280 * 720 5.0
- IP65 / 1.5m
- 8000 3.7
- 8
- 4G /
- 1D / 2D
- TCS1SM

OCBS-D5000:

OCBS-D5000	
OCBS-D5000 -	
OCBS-D5000	170mm (h) x85mm (w) x23mm (d) 2
OCBS-D5000	380 :g ()
OCBS-D5000	720 - . 5.0 x1280
OCBS-D5000	
OCBS-D5000	3 4 6
OCBS-D5000	2 1 1
OCBS-D5000	8000 3.7
OCBS-D5000	
OCBS-D5000	A53 1.5GHz
OCBS-D5000	5.1.1
OCBS-D5000	1GB 8 GB 32 GB
OCBS-D5000	
OCBS-D5000	-20 °C 50 °C
OCBS-D5000	-20 °C 70 °C
OCBS-D5000	5 RH 95
OCBS-D5000	5ft./1.5 m
OCBS-D5000	IP65

ESD	± 15kv 8 ± 0.000000 kv 8 0.000000 0.000000 kv 0.000000 0.000000	
0.0000 0.0000		
SDK	HHW 0.00000000 0.0000 0.000000	
0.00	0.0000	
0.0000	0.000000 0.000000 0.000000 0.0000	
0.00000000 0.00000000		
WWAN	4G 7 1 2 3 0.000000 0.0-0.0 40 39 38 0.000000 0.0-0.0. WCDMA (850/1900 / 2100MHz 0.0(0 1900 / 850/900/1800 0.0000 / 0.0 0.0 0.0 / 0.000MHz)0	
WLAN	2.4 802.11 0.000 0.00000000 0.00000000 0.0000 5 / 0.0000 a / b / g / n / 0.0	
WPAN	0.000 0.000000 v2.1 + 0.00000000 0.0000 v3.0 + 0.000 v4.0 0.000000	
GPS	0.0 0.000000 0.0 0.0000) 0.0 A-0 5 0.000 0.000	
0.00000000 CAPTUER		
0.00000000 READER (0.00000000)		
1D 0.00000000	1D 0.000000 0.0000	0.000000 N431x
	Symbologies	1 0.00000000 0.0000D 0.00000000
2D 0.00000000	2D 0.0000 0.0000	0.000000 N6603
	Symbologies	PDF417 0.0 MicroPDF417 0.0 39-0.000 0.0000 0.0000 0.000 0.000000 0.00000000 0.00000000 0.000 0.000000000000 0.000000 0.000000000 0.000000 0.00000000 0.00000000 0.00000000 0.00000000 0.00000000 0.00000000 0.00000000 0.000000 0.00000000 0.00000000 0.00000000 0.00000000 0.000 .0.00000000 0.000000 0.00000000 0.00000000 0.0000000000
0.0000 0.000 0.0000		
0.000000	0.0000000000 0.000000	
0.0000	0.000 0.0000 0.000 0.0000000000 0.00000000	
RFID READER (0.00000000)		
RFID LF	0.0000	125KHZ / 134.2KHz (FDX-B / HDX)
	0.00000000	ISO 11784 & 11785 0.000000
	R / W 0.0000	2CM 0.0 10 0.000
RFID HF	0.0000	13.56MHZ
	0.00000000	ISO 14443A & 15693 0.000000
	R / W 0.0000	2CM 8 0.000cm
RFID UHF	0.0000	865 ~ 868MHZ 925 ~ 920 0.00MHZ
	0.00000000	EPC C1 GEN2 / 6-18000 0.000C
	0.000 0.00000	2) 0.00000 0.00000dBi)
	R / W 0.0000	1 0.000000000 0.00000000 0.000000000) 0.000 1.5 0.000 0)
2.45 0.0000GHz	0.00000000) 0.000 200 0.0 0.0000 0.0000 0.0000)	
433MHz 0	0.00000000) 0.000 200 0.0 0.0000 0.0000 0.0000)	
0.000000 READER (0.00000000)		
0.00000000	IEEE 802.15.4 (0.00000000)	
0.0000 0.00000	100 m 200 0.000 m (0.00000000)	
0.0000 READER (0.00000000)		
0.00000000	TCS1SM	
0.0000 0.0000000000	0.00000000 0.00000000 0.00000000	
0.000000	508 DPI	
0.0000	0.005 0.0000 & 0.000 0.00000.008 0.0000 & 0.000	
0.000	1000	
PSAM SECURITY (0.00000000)		
0.00000000	ISO 7816	
0.0000 0.0000	9600 19200 38400 43000 56000 57600 115200	
0.0000	2 0.0000 0.0000) 0.000000	
0.00000000		

<p>□□□□□</p>	<p>1xPower □□□□□ □□□□□ □□□□□ □□□□□ 1xDC □□□ □□□□ 1XUSB □□□□□□□□ □□□□</p>
<p>□□□□□□□</p>	<p>□□□□□□ □□□ □□□ □□□□□ □□□□□</p>



OCBS-D5000



www.ocominc.com



□□□□□□□ □□□□□□□ □□□ □□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□□ □□□ □□□□