

OCBS-D5000

(M / N: OCBS-D5000)

OCBS-D5000

OCBS-D5000

- 5.1.1

- 1GB 8 GB

- 1280 * 720 5.0

- IP65 / 1.5m

- 8000 3.7

- 8

- 4G /

-

- 1D / 2D

-

- TCS1SM

OCBS-D5000:

OCBS-D5000	
OCBS-D5000 -	
OCBS-D5000	170mm (h) x85mm (w) x23mm (d) 2
OCBS-D5000	380 :g (g)
OCBS-D5000	720 - . 5.0 x1280
OCBS-D5000	
OCBS-D5000	3 4 6
OCBS-D5000	2 1 1
OCBS-D5000	8000 3.7
OCBS-D5000	
OCBS-D5000	A53 1.5GHz
OCBS-D5000	5.1.1
OCBS-D5000	1GB 8 GB 32 GB
OCBS-D5000	
OCBS-D5000	-20 °C 50 °C
OCBS-D5000	-20 °C 70 °C
OCBS-D5000	5 RH 95
OCBS-D5000	5ft./1.5 m
OCBS-D5000	IP65
ESD	± 15kv 8 ± kv 8 kv
OCBS-D5000	
OCBS-D5000	

SDK	HW	
WWAN	4G LTE Cat. 3 40 39 38 WCDMA (850/1900 / 2100MHz) 1900 / 850/900/1800 / MHz	
WLAN	2.4 802.11 5 / a / b / g / n /	
WPAN	v2.1 + v3.0 + v4.0	
GPS	A- 5	
CAPTURER		
READER ()		
1D	1D	N431x
	Symbologies	1 D
2D	2D	N6603
	Symbologies	PDF417 MicroPDF417 39- PDF417
RFID READER ()		
RFID LF		125KHZ / 134.2KHz (FDX-B / HDX)
		ISO 11784 & 11785
	R / W	2CM 10
RFID HF		13.56MHZ
		ISO 14443A & 15693
	R / W	2CM 8 cm
RFID UHF		865 ~ 868MHZ 925 ~ 920 MHz
		EPC C1 GEN2 / 6-18000 C
		2) dBm
	R / W	1 () 1.5 ()
2.45 GHz	() 200 ()	
433MHz	() 200 ()	
READER ()		
	IEEE 802.15.4 ()	
	100 m 200 m ()	
READER ()		
	TCS1SM	
	508 DPI	
	0.005 & 0.008 &	
	1000	
PSAM SECURITY ()		
	ISO 7816	
	9600 19200 38400 43000 56000 57600 115200	
	2 ()	

<p>□□□□□</p>	<p>1xPower □□□□□ □□□□□ □□□□□ □□□□□ 1xDC □□□ □□□□ 1XUSB □□□□□□□□ □□□□</p>
<p>□□□□□□□</p>	<p>□□□□□□ □□□ □□□ □□□□□ □□□□</p>



OCBS-D5000



www.ocominc.com



□□□ □□□□ □□□□ □□□□□□□□ □□□□ □□ □□□□□□□□