

([[]]:OCBS-L006)

00000000:

	670-650) [[[[]] [[][nm]]
	2.5 ~ 600MM (100□ UPC / EAN)
	0.10mm (4mil) ∏ PCS 0.9
	200 650 @) 0000 000 0000 0000NM)
	UPC / EAND UPC / EAN 0000000 000 UCC / EAN1280 00000 039 00000
	39 ASCII 39 0000 0000 trioptic 128 0000 0128 00000 ASCII 0000
	93 0000 05 00 2 00000 05 00 2 0000 00000 MSIO 11 000000
	ATAD 00000000 RSSD 5 00 2 0000000
<u>0000000000 0000000</u>	
	PS2[] RS232[] USB
	DC + 5V +/- 5[]
	0000 00 000000 0000000 (RS232) 000000 0000000
<u> </u>	
	L165.42mm X W69.72mm X H89.67mm
	140G (00000 0000)
<u> </u>	
<u>0000000 00000 0000:</u>	-40 0000 000 70 ~ 0000 000
	5 ~ 0000 00 0095 000000 000000
	15 00000 00000 -/+0 00000KV 8 -/+0KV 0000000 0000000 00
	1.5 0000 00000M 000000 000000
EMI / RFI:	FCC [] ([]) [][][][CE
	0000 CDRH 00000 2 00000



Product Picture





Features

www.ocominc.c

Simple but not easy

High scan rate and long reading distance; www.ocominc.com





All-round show





Parameter

Performance Characteristics		
Light Source:	Visible laser (650-670nm)	
Scan Rate:	100 scans per second	
Reading Distance	2.5~600mm (100% UPC/EAN)	
Scanner Type:	Bi-directional	
	t. m :	

Resolution:	0.10mm (4mil) at PCS 0.9			
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)			
Decode Capability:	UPC/EAN, UPC/EAN with supplemental, UCC/EAN128, code 39, code 39 full ASCII, code 3 trioptic, code 128, code 128 full ASCII, coda bar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5			
Physical Characteristics				
Interfaces Supported:	PS2, RS232, USB			
Voltage:	DC+5V+/-5%			
Current:	100 mA			
Idle Current:	<40 mA			
Power Source:	Host power or external (RS232) power supply			
Scanning Angle	Inclination 45° Elevation 60°			
Dimensions:	L165.42mm X W69.72mm X H89.67mm			
Weight:	140g (without stand)			
Stand	Without			
Color:	Ivory and black			
User Environment	- $ -$			
Operating Temperature:	0 Degree C∼50 Degree C			
Storage Temperature:	-40 Degree C~70 Degree C			
Humidity:	5~95% relative humidity, non-condensing			
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge			
Drop Specifications:	Withstands multiple 1.5m drops to concrete			
Safe:				
EMI/RFI:	FCC Class A and CE			
Laser Safety:	CDRH class 2 laser product			

Production Line





Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
V0	Thermal Printer	40,000 Sets / Month	250,000 Sets
1	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
V	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
1	POS Machine	5,000 Sets / Month	10,000 Sets
1	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

√ Indicates information has been verifed onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and

services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	0///
✓	Calliper	GUANGLU	2
√ ∠CO	Multi-meter	VC890D	7
1 M.	Test Computer	No Information	13

√ Indicates information has been verifed onsite by TUV on 2013.7.15

Certifications





Packing and Shipment





Payment

















Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Why you choose us?



Flexible Cooperation

Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust









OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.




OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big supprise is waiting for you. w.ocomith

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,

Shenzhen 518054, China;

Websites: http://www.possolution.com.cn; http://www.ocominc.com;

E-mail: ocom@ocominc.com, ocomtech@gmail.com;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637,190852203; Tel/Fax: +86.755.8605.3207.

