

〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇 〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇
 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇
 (ModelNo .: OCBS -LA01)

〇〇〇〇〇:

- 〇 〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇 〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇.
- 〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇
- 〇 〇〇〇〇〇〇〇 〇 decodecapability.
- 〇 KBW 〇 RS232 〇 USB 〇 〇〇〇〇〇〇
- 〇 〇〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇 〇〇〇〇〇 〇〇〇〇〇 〇

〇〇〇〇〇:

〇〇〇〇〇〇〇 〇〇〇〇〇〇〇	
〇〇〇 〇〇〇〇:	〇 〇 670-650) 〇〇〇〇 〇〇〇〇)
〇〇〇〇:	100 〇〇〇〇〇〇〇〇〇 〇〇〇 (SPS)
〇〇〇〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇〇〇〇	8 〇〇
〇〇〇〇〇 〇〇〇〇	3〇000〇000 / 1 〇〇 〇〇〇
〇〇〇〇〇〇〇 〇〇〇〇〇	2.5 ~ 600mm
〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇:	〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇
〇〇〇〇〇〇:	0.10mm (4mil) 〇〇 PCS 0.9
〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇〇〇:	20 〇 〇 〇〇〇 〇〇〇〇〇 650) 〇〇〇〇 〇〇〇〇 〇〇〇)
〇〇〇〇〇 〇〇〇〇〇	60 〇〇〇〇〇〇〇〇〇 〇〇〇〇〇 〇° 45 〇〇〇〇〇 〇〇〇〇〇 〇°
〇〇〇〇〇〇〇 〇〇 〇〇〇 〇〇〇〇〇〇:	UPC / EAN 〇 UPC / EAN 〇〇〇〇〇〇〇〇〇 〇〇 〇 UCC / EAN128 〇 〇〇〇〇〇〇 〇〇〇〇 39 〇〇〇〇〇 〇 39 ASCII 〇 39 〇〇〇〇〇〇 trioptic 〇 128 〇〇〇 〇 code 128 full ASCII 〇 codabar 〇 〇〇〇〇〇〇 〇 5 〇〇 2 〇〇〇〇〇 〇 5 〇〇 2 〇〇〇〇〇 93 〇 MSI 〇 11 〇〇〇 〇 ATA 〇 〇〇〇〇〇〇〇 RSS 〇 5 〇〇 2 〇〇〇〇〇〇〇〇 ...
〇〇〇〇〇 〇〇〇〇〇:	〇〇〇〇〇〇〇〇〇 〇〇〇〇〇 〇〇 〇〇〇〇
〇〇〇〇〇〇〇 〇〇〇〇〇〇〇	
〇〇〇〇〇〇〇〇 〇〇〇〇〇〇:	PS2 〇 RS232 〇 USB
〇〇〇〇〇〇〇〇 〇〇〇〇〇:	DC 5V + +/- 5 〇
〇〇〇〇:	110 :〇〇〇〇〇〇〇 〇〇〇〇 〇 〇〇〇〇〇〇 〇〇〇〇 100 :〇〇〇〇〇〇〇mA
〇〇〇〇〇〇 〇〇〇〇〇:	& lt;〇〇〇〇〇〇 〇〇〇〇 30 〇
〇〇〇〇〇〇 〇〇〇〇:	〇〇〇〇〇 〇〇〇〇 〇〇〇〇 〇〇 〇〇〇〇〇〇〇 〇〇〇〇 (RS232)
〇〇〇〇〇	L200mm × W72mm × H58.5mm
〇〇〇	480 〇〇〇〇〇〇〇 〇〇) 〇〇〇〇)
〇〇〇〇:	〇〇

□□□□:	□□□□ □□ □□□
□□□□□□□□ □□□□	
□□□□□□□ □□□□□ □□□□:	0 ~ 40 □□□□□ □□□□
□□□□□□□ □□□□□ □□□□:	-30 ~ 60 □□□□□ □□□□
□□□□□:	5 ~ 95 □ □□□□□ □□□ □ □□□□□□□ □□□□□□□
□□□□□□□ □□□□□□□ □□□□□□□□	□□□□□□ □□□□□ pos □□□□□□□□ □□□□□□□□ □□□□□□□ □□□□ □□ □□□□□□□ □□ □□□□ □ □□□□□□□□ pos □□□□□ □□□□□ □□□□□□□□ □□□□□□□□
□□□□□□□□□□ □□□□□□□□	□□ □□□□□□□□ air 15KV 8 ± □ □□□□□□□ □□□□□□□□KV □□□□□□ □□□□□□□□ □□
□□□□□□□□□□ □□□□□:	□□□□□□□□□ □□□ □□□ 1.5 □□□□□□ □□□□ □□□□□□
□□□□:	
EMI / RFI:	FCC Class B and CE
□□□□□□ □□□□□:	2 □□□□ (IEC60825-1 □ EN60825-1)



OCBS-LA01



www.ocominc.com

