

1D Barcode Reader  
 (ModelNo.: OCBS-LA01)

Features:  
 - High speed 1D barcode reading  
 - Support various barcode formats  
 - decode capability.  
 - KBW - RS232 - USB - interface  
 - Compact size

Specifications:

General Information	
Model No.:	OCBS-670-650 (Barcode Reader)
Capacity:	100 SPS (SPS)
Barcode formats supported:	8 formats
Barcode length:	3000 / 1 mm
Barcode width:	2.5 ~ 600mm
Barcode height:	Adjustable
Resolution:	0.10mm (4mil) PCS 0.9
Barcode format supported:	20 formats (650) Barcode Reader
Barcode angle:	60 degrees (45 degrees)
Barcode types supported:	UPC / EAN - UPC / EAN - UCC / EAN128 - code 39 - ASCII - trioptic - 128 code - 128 full ASCII - codabar - 5 - 2 - 5 - 2 - 93 - MSI - 11 - ATA - RSS - 5 - 2 ...
Barcode type:	Barcode Reader
Interface	
Interface:	PS2 - RS232 - USB
Power supply:	DC 5V + +/- 5V
Current:	110 mA (100 mA)
Weight:	< 30g
Barcode type:	Barcode Reader (RS232)
Dimensions:	L200mm x W72mm x H58.5mm
Barcode type:	480 Barcode Reader
Barcode type:	Barcode

□□□□:	□□□□ □□ □□□
□□□□□□□□ □□□□	
□□□□□□□ □□□□□ □□□□:	0 ~ 40 □□□□□ □□□□
□□□□□□□ □□□□□ □□□□:	-30 ~ 60 □□□□□ □□□□
□□□□□:	5 ~ 95 □ □□□□□ □□□ □ □□□□□□□ □□□□□□□
□□□□□□□ □□□□□□□ □□□□□□□□	□□□□□□ □□□□□ pos □□□□□□□□ □□□□□□□□ □□□□□□□ □□□□ □□ □□□□□□□ □□ □□□□ □ □□□□□□□□ pos □□□□□ □□□□□ □□□□□□□□ □□□□□□□□
□□□□□□□□□□ □□□□□□□□	□□ □□□□□□□□ air 15KV 8 ± □ □□□□□□□ □□□□□□□□KV □□□□□□ □□□□□□□□ □□
□□□□□□□□□□ □□□□□:	□□□□□□□□□ □□□ □□□ 1.5 □□□□□□ □□□□ □□□□□□
□□□□:	
EMI / RFI:	FCC Class B and CE
□□□□□□ □□□□□:	2 □□□□ (IEC60825-1 □ EN60825-1)



OCBS-LA01



[www.ocominc.com](http://www.ocominc.com)

