

السيارات تحسس ماسح الباركود المحمولة مع موقف  
(الموديل: OCBS -LA06)

□□□□□:

| خصائص الأداء                |                                                                                                                                                                                                                                               |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| مصدر ضوء:                   | (ليزر مرئي (650-670 ن م                                                                                                                                                                                                                       |
| الانعكاس:                   | مسح في الثانية 100                                                                                                                                                                                                                            |
| قراءة المسافة:              | 2.5 ~ 600mm (100% UPC / EAN)                                                                                                                                                                                                                  |
| نوع الماسح الضوئي:          | ثنائية الاتجاه                                                                                                                                                                                                                                |
| القرار:                     | 0.10mm (4mil) في PCS 0.9                                                                                                                                                                                                                      |
| الحد الأدنى لطباعة التباين: | 20% ، 650) (nm فرق عاكس دنيا                                                                                                                                                                                                                  |
| قدرة فك التشفير:            | الكود ، 128 ، كود 128 ، trioptic كود 39 ، ASCII 39 ، كود 39 كامل ، UCC / EAN128 ، مع الإضافات UPC / EAN ، UPC / EAN ، كود 128 ، معشق 2 من 5 ، منفصل 2 من 5 ، كود 93 ، ASCII كامل ، MSI ، الصينية 2 من 5 ، RSS خلاصات ، ATA ، رمز 11 ، MSI ... |
| الخصائص البدنية             |                                                                                                                                                                                                                                               |
| واجهات المدعومة:            | PS2 ، RS232 ، USB                                                                                                                                                                                                                             |
| الجهد الكهربائي:            | DC 5V + +/- 5%                                                                                                                                                                                                                                |
| تيار:                       | مللي أمبير 100                                                                                                                                                                                                                                |
| التيار الخمول:              | & lt40 ؛ mA                                                                                                                                                                                                                                   |
| مصدر الطاقة:                | (RS232) طاقة المضيف أو مصدر طاقة خارجي                                                                                                                                                                                                        |
| زاوية المسح:                | الميل 45 درجة الارتفاع 60 درجة                                                                                                                                                                                                                |
| الأبعاد:                    | L165.42mm X W69.72mm X H89.67mm                                                                                                                                                                                                               |
| وزن:                        | (غرام (بدون حامل 140                                                                                                                                                                                                                          |
| يفهم:                       | مع                                                                                                                                                                                                                                            |
| اللون:                      | العاج والسوداء                                                                                                                                                                                                                                |
| بيئة المستخدم               |                                                                                                                                                                                                                                               |
| درجة حرارة التشغيل:         | 0degree C ~ 50degree C                                                                                                                                                                                                                        |
| درجة حرارة التخزين:         | -40degree C ~ 70degree C                                                                                                                                                                                                                      |
| رطوبة:                      | الرطوبة النسبية ، دون تكاثف % 5 ~ 95                                                                                                                                                                                                          |
| التفريغ الكهربائي:          | من تفريغ الاتصال KV +/- 8 تأكد من تفريغ الهواء +/- 15                                                                                                                                                                                         |
| إسقاط المواصفات:            | تتحمل عدة قطرات 1.5 متر إلى الخرسانة                                                                                                                                                                                                          |
| أمن:                        |                                                                                                                                                                                                                                               |
| EMI / RFI:                  | FCC Class A و CE                                                                                                                                                                                                                              |
| سلامة الليزر:               | فئة 2 الليزر المنتج CDRH                                                                                                                                                                                                                      |

□□□□□ □□□□□:

**ocom**  
All your side

*Handheld Laser  
Barcode Scanner*

**OCBS-LA06**



**Product Picture**





## Features

**Simple but not easy**

Auto-Induction built in, green design



High scan rate and long reading



distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with future-proofing



## || All-round show





## Parameter

| Performance Characteristics |                                                                                                                                                                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light Source:               | Visible laser (650-670nm)                                                                                                                                                                                                                |
| Scan Rate:                  | 100 scans per second                                                                                                                                                                                                                     |
| Reading Distance            | 2.5 ~600mm (100% UPC/EAN)                                                                                                                                                                                                                |
| Scanner Type:               | Bi-directional                                                                                                                                                                                                                           |
| Resolution:                 | 0.10mm (4mil) at PCS 0.9                                                                                                                                                                                                                 |
| Print Contrast Minimum:     | 20%, minimum reflective difference (@650nm)                                                                                                                                                                                              |
| Decode Capability:          | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| Physical Characteristics    |                                                                                                                                                                                                                                          |

|                          |                                                                  |
|--------------------------|------------------------------------------------------------------|
| Interfaces Supported:    | PS2, RS232, USB                                                  |
| Voltage:                 | DC+5V+/-5%                                                       |
| Current:                 | 100 mA                                                           |
| Idle Current:            | <40 mA                                                           |
| Power Source:            | Host power or external (RS232) power supply                      |
| Scanning Angle           | Inclination 45° Elevation 60°                                    |
| Dimensions:              | L165.42mm X W69.72mm X H89.67mm                                  |
| Weight:                  | 140g (without stand)                                             |
| Stand                    | With                                                             |
| Color:                   | Ivory and black                                                  |
| <b>User Environment</b>  |                                                                  |
| Operating Temperature:   | 0°C~50°C                                                         |
| Storage Temperature:     | -40°C~ 70°C                                                      |
| Humidity:                | 5~95% relative humidity, non-condensing                          |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications:     | Withstands multiple 1.5m drops to concrete                       |
| Safe:                    |                                                                  |
| EMI/RFI:                 | FCC Class A and CE                                               |
| Laser Safety:            | CDRH class 2 laser product                                       |

## Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.





## **الوثائق ذات الصلة:**

الوقود النووي؟ رجااء انقر هنا information تريد معرفة المزيد من المنتجات

[تخصيص](#)

[دليل المستخدم](#)