

2D Omni-Directional Barcode Scanner

□M/N: OCBS -T207□

سمات:

Support Multiple kinds of 1D and 2D barcodes;
4mil scanning resolution;
480*640 CMOS Sensor;
Easy to scan screen barcodes.

تخصيص

| | |
|----------------------------|---|
| عام | |
| نموذج | OCBS -T207 |
| اللون | orange+أسود/blue+أسود/red+black for optional |
| IP grade | IP52 |
| مادة | ABS+PC |
| Processor | 32-bit ARM MCU |
| واجهه المستخدم | USB |
| Invoices | الدعم |
| مؤشر | Buzzer+Lamp indicator□فاد□ |
| مزود الطاقة | DC 5V ±5% |
| Electric current | 200mA□231□□تعليقmA□290□□عملmA□أقصى□ |
| استهلاك الطاقة | 1.0W□1.16□□تعليقW□1.45□□عملW□أقصى□ |
| لغة | AmericanEnglish;Belgium;Brazil;Canada (French);Denmark;Finland,(Swedish);TheFrench;Germany/Austria;Greece;Hungary;Israel (Hebrew);Italy;LatinAmerica;Dutch (Dutch);Norway;Poland;Portugal;Romania;Russia;Spain;Sweden;Switzerland(German);TurkeyF;TurkeyQ;The UK;Japan [support virtual keyboard] |
| OS Support | Linux□ماك□.10□.8□.7□بي□وويندوز□إكس بي□ |
| Electrostatic Protection | 15KVair charging |
| Shock Resistance | Drop Test 1.2m□ concrete surface□ |
| أداء | |
| المستشعر | CMOS sensor |
| Moving Tolerance | 25cm/sec(10mil QR code) |
| Reading Angles | Roll360°, Pitch45°,Yew60° |
| Scanning Angles | 32°* 30° |
| التباين | ≥30% |
| Ambient light illumination | 0~100000LUX |
| نسبة الخطأ | 1/500Million |
| Reading Mode | صورة |
| وضع الزناد | Auto-Sensing |
| دقة | Code39 4mil |
| Scanning Depth | Code39 4.17mil□15 bytes□□ 7cm - 13cm Code39 10.83mil□16 bytes□□8cm - 15cm Data Matrix 10.83mil□8 bytes□□ 6cm - 11cm Code QR 10.83mil□8 bytes□□ 5cm - 13cm |
| Decoding ability | 1D:Code 128, EAN-8,Code 39,EAN-13,UPC-E0,Code 93, UPC-E1,UPC-A, Plessey, Interleaved 2 of 5, Industrial 25, Standard 25, Codabar, MSI-Plessey, UPCE0/E1, GS1-128, GS1 Databar, Matrix 2 of 5,ITF-14, Code32,Code 11,ISBN, ISSN,Standard 25, 2D:Data Matrix ,QR,PDF417 |

| | |
|-----------------------------|--|
| بدني | |
| وزن | Gross:200g |
| طرد | 190*180*123mm |
| 20 in 1 carton | 645*390*400mm/11.3kg |
| بيئته | |
| درجة حرارة العمل والرطوبة | 0 to 45 degrees centigrade, 10%~80% No condensation |
| درجة حرارة التخزين والرطوبة | -20 to 60 degrees centigrade , 10%~90% No condensation |





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207





OCBS-T207

