المسافة الطويلة لاسلكي محمول رمز الاستجابة السريعة ماسح OCBS-W230 الباركود

(OCBS-W230)

	95x65x155mm
	ABS + PC
000000 00000	160G

	617 00000 000				
	625 00000 000				
	39 ° (H) × 25 °				
	0-360 °				
	± 65 [][][]				
000 0000	± 60 □□□□	± 60 [][]			
	25 🔲 🔲 🖂				
1D		UPC / EAN[] UPC / EAN [][][][][] BooklandEAN[] ISSN[] UCC [][][][][][][][][][][][][][][][][][][
		93			
	Codabar[] MSI[] 5 [[[] 2 [[[[[[] DataBarvariants GS	2 DODOOD DataBarvariants GS1 5 D 3 DODOOD ISBT CONCAT		
2D PDF417□ MicroPD		PDF4170 0000000 00000 TLC-390 00	4170 0000000 00000 TLC-390 000000 0000000 Maxicode0 000		
		DOOD MicroQRD DOOD			
	00 00 00				
		M. 300 :0000000M (0000)	<u> </u>		
	-10 °C - 45 °C				
000000 50 -850					
	5 -95				
		C 5V[] 350MA			
			86000 :		
EMC EN50081 par1 0000					
00000000 00000000 0000 EN500820 par1 00000			<u></u>		
IP [] [] [P42					
00 000000	T				
00000 0000 *					
		HD 000000 0000			
		5)()			
39 [[[[]]]]	5.0 [[]	5MM	90		
100 UPCA	13.0 🔲	8MM	200MM		
39 [[[[]]]	20.0 🔲	8MM	250MM		
PDF 417	6.8 []	5MM	95MM		
	10.0 [5MM 10MM	110MM 150MM		
1,00000 20,00000	20.0 🔲		INIMING		
1 0000 39 0000		2.8 0.071) [[mm]			
2 0000000 000000 0000D		4.8 0.122) □□mm)			



