

OCBS -W230 OCBS -W230 USB

(OCBS -W230)

OCBS -W230	95x65x155mm
Material	ABS + PC
Capacity	160G

LED	617 617 LED
LED	625 625 LED
Power	39 39 25 × (V)
Temperature	0 - 360 0 - 360
Accuracy	± 65 ± 65
Accuracy	± 60 ± 60
Accuracy	25 25
1D	UPC / EAN UPC / EAN BooklandEAN ISSN UCC Coupon Extended Code Code128 GS1-128 ISBT 128 Code 39 Code 39 FullASCII Trioptic Code 39 Code 32 Code 93 Code11 Matrix 2 of 5 Interleaved 2 of 5 Discrete 2 of 5 Codabar MSI Chinese 2 of 5 GS1 DataBarvariants Korean 3 of 5 ISBT Concat
2D	PDF417 MicroPDF417 Composite Codes TLC-39 Data Matrix Maxicode QR Code MicroQR Aztec
Temperature	300 : 300 100 : 100
Temperature	-10 °C - 45 °C
Temperature	-20 °C - 65 °C
Temperature	5 - 85
Temperature	5 - 95
Temperature	1.8 1.8
Power	DC 5V 350mA
Lumination	86000 : 86000 3.000 : 3.000 LUX
EMC	EN50081 PAR1
FCC	EN50082 PAR1
IP	IP42

DECODE RANGES

OCBS -W230 *	OCBS -W230	OCBS -W230	OCBS -W230
			HD
39	5.0	5MM	90mm
100 UPCA	13.0	8MM	200MM
39	20.0	8MM	250MM
PDF 417	6.8	5MM	95MM
	10.0	5MM	110MM
	20.0	10MM	150MM
1 D 39		2.8 (0.071)	
2 D		4.8 (0.122)	

