الباركود مع مهد Dأو بلوتوث لاسلكية رمز الاستجابة السريعة 2 MHZعالية الجودة 433

نموذج: OCBS-W231-4 / B

ميزات:
Mداخلي. بلوتوث لاسلكي عن بعد الاتصالات 20 Mفي الهواء الطلق، 100 Mاللاسلكي المسافة الاتصالات 300 1MHz، 433
في الأماكن المغلقة. Mفي الهواء الطلق، و10
2، مجهزة الاتصالات وقاعدة شحن
3، البلاستيك اللين غطاء لحماية العدسة والخطوط العريضة مما يعزز من أداء مكافحة الإفلات.
4، الباركود على أجهزة الكمبيوتر "والهواتف المحمولة" الشاشة يمكن مسحها.
5، لا حاجة سائق، التوصيل والتشغيل.
6، يمكن تخزين أكثر من 10،000 قطعة من البيانات؛
433) 7MHZ)، والماسحات الضوئية متعددة يمكن توصيل جهاز استقبال واحد.

المعلمات:

تهدف مصدر الضوء	617 نانومتر الصمام		
مصدر الإضاءة الخفيفة	625 نانومتر الصمام		
زاوية المسح الضوئي	39 ° (H) × 25 ° (V)		
زاوية الدوران	0-360 °		
زاوية الارتفاع	65 درجة ±		
زاوية ميل	60 درجة ±		
طباعة التباين	25 أعلى من ٪		
1D	UPC / EAN، UPC / EAN مع المكملة، BooklandEAN، ISSN، UCC القسيمة الموسعة، Trioptic كامل ASCII، 39 قانون 39، قانون ISBT 128، GS1-128، CODE128، المدونة 93 قانون 32، قانون 39، قانون Code11، المنفصل 5 من 2، معشق 5 من 2، ماتريكس الصينية 2 من 5، GS1 Barvariants 5 من 3 والكورية البيانات، ISBT CONCAT، MSI، Codabar، 2of 5		
2D	PDF417، MicroPDF417، رموز المركبة، TLC-39، مصفوفة بيانات، Maxicode، رمز الاستجابة السريعة، MicroQR، ازتيك		
جهة تعامل	USB (كابل استقبال Wirelless)		
بعد الاتصالات	433MHZ: 100 Mفي الداخل: 300 Mالخارجية (ماكس) بلوتوث: في الداخل: 10 Mالخارجي: 20 M (ماكس)		
درجة حرارة التشغيل	-10 درجة مئوية - 45 درجة مئوية		
درجة حرارة التخزين	-20 درجة مئوية - 65 درجة مئوية		
رطوبة العملية	5٪ -85٪		
تخزين الرطوبة	5٪ -95٪		
متانة	1.5 Mيقاوم متعددة قطرات لملموسة		
مدخل الطاقة	DC 5V، 280mA		
وقت الشحن	6H		
البطارية	1500mAh بطارية		
Lumination	3.000 في الداخل: LUX 86000 ضوء الشمس الخارجي. كحد أقصى LUX ماكس		
الصف IP	IP42		
نطاقات فك			
* أداء نموذجي		نطاقات العمل النموذجية	
		نطاق التركيز HD	
بار كود نوع	رمز الكثافة	قريب	بعيدا
39 قانون	5.0 مل	5MM	90 ضرباتmm
100٪ UPCA	13.0 مل	8MM	200MM

قانون 39	مل 20.0	8MM	250MM
PDF 417	مل 6.8	5MM	95MM
مصفوفة البيانات	مل 10.0	5MM	110MM
رمز الاستجابة السريعة	مل 20.0	10MM	150MM
قانون 39 Dقرار 1	مل 4		
Dقرار مصفوفة البيانات 2	مل 10		
مواد	ABS + PC		
البعد	168 * 95 * 70) الماسح الضوئي mm) 74 * 112 * 145) قاعدة mm)		
الوزن الصافي	186 الماسح الضوئي g 185 قاعدة g		
معلومات الطلبية:	**OCBS-W231-4:** 433MHz 2 اللاسلكي ماسح الباركود Dمع مهد		
	OCBS-W231-B: بلوتوث الماسح الضوئي barocde 2D مع مهد		

FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE

LONG DISTANCE WIRELESS COMMUNICATION

STRONG DECODING ABILITY

CHARGING CRADLE

STABLE STRUCTURE

NO NEED DRIVER, PLUG AND PLAY

1 FAST SCAN,HIGH RECOGNITION RATE

3 CRADLE FOR CHARGING AND WIRELESS COMMUNICATION

4 STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE

5 NO NEED DRIVER PLUG AND PLAY

The product family

Product packaging figure

WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER

PRODUCT INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wirelless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base(145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.