مع موقف dعاليه الجودة 433 ميغاهيرتز أو بلوتوث لاسلكيه كودا قطريا الماسح الضوئي 2

ب/4-W231-نموذج: اوكبس

:

1 ، 433 100 المسافة إلى بلوتوث لاسلكيه في m ميغاهيرتز لاسلكيه مسافة الاتصال 300 متر في الهواء الطلق ، والداخلية ؛
الهواء الطلق 20 م و 10 متر داخلي ؛
2 ، مجهزه بالشحن والاتصال
3 ، والغطاء البلاستيكية لينه لحماية العدسة والخطوط العريضة يحسن بشكل كبير من أداء المضادة للتسرب ؛
4 ، يمكن مسح الرموز الشريطية الموجودة علي شاشه أجهزه الكمبيوتر والهواتف المحمولة ؛
5 ، لا تحتاج السائقين ، والتوصيل والتشغيل ؛
6 ، يمكن تخزين أكثر من 10 000 قطعه من البيانات ؛
7) ، يمكن توصيل ماسحات ضوئيه متعددة إلى جهاز استقبال واحد (433 ميغاهيرتز.

:

وجود مصدر الضوء	617 نانومتر		
أضاءه مصدر الضوء	625 نانومتر		
زاوية المسح الضوئي	39 ° (ت) 25 ° (ارتفاع)		
زاوية التناوب	0-360 °		
زاوية الارتفاع	65 °		
زاوية أماله	60 °		
تباين الطباعة	اعلي من 25 في المائة		
مد 1	اتحاد الوطنيين الكونغوليين/الين ، اتحاد الوطنيين الكونغوليين/الين مع التكميليات ، الكتب ايفاز 128 ، رمز 39 ، ، gs1-128 ، Code128 القسيمة الموسعة الحرة ، issn ، المرجعية رمز 39 الثلاثي ، رمز 93 ، رمز 32 ، 11 ، مصفوفة 2 5 ، تعشيق 2 ، ascii رمز 39 كامله الكورية 3 5 ، ، gs1 ، البيانات البديلة ، 5 ، 2-5 ، msi ، من 5 ، والمنفصلة 2 من 5 ، كودابار التقعر المقعرة		
2d	داتاتاترياكس ، ماككود ، رمز ، tlc-39 ، رموز معقده ، MicroPDF417 ، PDF417 نوع من ريال قطري ، الازتيك ، مايكرو		
واجهه	(الناقل التسلسلي العام (كابل الاستقبال لاسلكي		
نطاق الاتصالات	433 100 ميغاهيرتز: الداخل: m; 300 الخارج: m ((كحد اقصي (بلوتوث: الداخل: 10 م ؛ الخارج: 20 مترا (كحد اقصي		
درجه حرارة التشغيل	45-درجه مئوية 10- درجه مئوية		
درجه حرارة التخزين	65-c درجه مئوية 20- °		
الرطوبة التشغيلية	85-5 في المائة		
محتوي الرطوبة اثناء التخزين	5%-95%		
ومتانة	1.5 يمكن ان تحمل مجموعه متنوعة من m إلى الخرسانة		
مدخلات الطاقة	5 v dc, 280 ma		
وقت الشحن	6 ح		
بطارية	150 ماه		
أناره	الداخل: 3,000 لوكس ماكس ؛ ضوء الشمس: ماكس 86000 لوكس		
الملكية الفكرية الصف	ip42		
نطاقات فك الترميز			
* أداء نموذجي		نطاقات التشغيل النموذجية	
		hd نطاق التركيز	
نوع الكود الشريطي	كثافة الرموز	قرب	كثير

الرمز 39	ميل 5.0	مم 5	مم 90
في المائة من الرموز 100 الشريطية للاوكا	ميل 13.0	مم 8	مم 200
الرمز 39	ميل 20.0	مم 8	مم 250
قوات الدفاع الشعبي 417	ميل 6.8	مم 5	مم 95
مصفوفة البيانات	ميل 10.0	مم 5	مم 110
ريال قطري لرمز	ميل 20.0	مم 10	مم 150
القرار 1 دال الرمز 39	مل 4		
القرار من مصفوفة البيانات 2d	مل 10		
مواد	abs + pc		
بعدا	74 * 112 * 145) القاعدة (مم 168 * 95 * 70) الماسح الضوئي mm)		
الوزن الصافي	185 ماسحه g 186 قاعده g		
طلب المعلومات:	ماسحه الباركود لاسلكيه 433 ميغاهيرتز من المهد 2d **:W231-4-اوكبس**		
	الماسح الضوئي مع المهد بلوتوث باروكدي 2d**ب: W231-2-اوكبس**		

FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE

LONG DISTANCE WIRELESS COMMUNICATION

STRONG DECODING ABILITY

CHARGING CRADLE

STABLE STRUCTURE

NO NEED DRIVER, PLUG AND PLAY

1 FAST SCAN,HIGH RECOGNITION RATE

3 CRADLE FOR CHARGING AND WIRELESS COMMUNICATION

4 STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE

5 NO NEED DRIVER PLUG AND PLAY

The product family

Product packaging figure

WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER

PRODUCT INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wirelless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base(145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: ocomsales15;

Whatsapp: +0086.189.4879.9080;