

## ريال قطري مع المهده المحمولة اليدوية لاسلكية الرمز الشريطي الماسح الضوئي 2

### w231-الموديل: اوكبس

- :
- الاتصالات لاسلكية بلوتوث مسافة 20 متر في m; ميغاهيرتز لاسلكية مسافة 300 متر في الهواء الطلق, الداخلية 100 433 1, الهواء الطلق , و 10 م داخليا ;
  - 2 , مجهزه بقاعده الاتصالات والشحن
  - 3 , والغطاء البلاستيكي لينة لحماية العدسة والخطوط العريضة يعزز إلى حد كبير الأداء المضاد للتسرب ;
  - 4 , ويمكن مسح الباركود علي أجهزه الكمبيوتر والهواتف النقالة ' الشاشة ;
  - 5 , لا حاجة السائق , والتوصيل واللعب ;
  - 6 , يمكن تخزين أكثر من 10,000 قطعه من البيانات ;
  - (7) , يمكن توصيل مساحات ضوئية متعددة إلى جهاز استقبال واحد (433 ميغاهرتز

:

استهداف مصدر الضوء	نانومتر 617		
أضائه مصدر الضوء	نانومتر 625		
زاوية المسح	(ارتفاع) × 25 ° (ت) 39 °		
زاوية الاستدارة	0-360 °		
زاوية الارتفاع	± 65 °		
زاوية أماله	± 60 °		
تباين الطباعة	اعلي من 25 في المائة		
1d	اتحاد الوطنيين الكونغوليين/الين , اتحاد الوطنيين الكونغوليين/الين مع التكميليات , الكتب ايسبريتيش 128 , رمز , gs1-128 , Code128 , القسيمة الموسعة رمز , issn , المرجعية الرمز الثلاثي 39 , رمز 32 , رمز 93 , 11 , مصفوفة 2 من 5 , , 39 ascii , رمز 39 كامل البيانات البديلة , gs1 , الصينية 1 من 5 , msi , التعشيق 2 من 5 , 2 المنفصلة 5 , كودابار الكورية 3 من 5 , المقعرة		
2d	مصفوفة البيانات , مايككود , رمز , tlc-39 , الرموز المركبة , MicroPDF417 , PDF417 , ريال قطري , مايكرو , الازتيك		
واجهه	(الناقل التسلسلي العام (الكابل الاستقبال السلكي		
مسافة اتصال	الخارج: 300 متر (كحد اقصي) ; m; ميغاهرتز: داخل: 100 533 (بلوتوث: الداخل: 10 م ; الخارج: 20 مترا (كحد اقصي)		
درجه حرارة التشغيل	ديغ سي-45 -10		
درجه حرارة التخزين	خ ع-65 خ ع -20		
الرطوبة التشغيلية	5%-85%		
رطوبة التخزين	5%-95%		
متانة	إلى الخرسانة m يقف العديد من قطرات 1.5		
طاقة الإدخال	280 , ma العاصمة 5 خامسا ,		
وقت الشحن	ح 6		
بطارية	ماه 150		
أناره	الداخل: 3.000 لوكس ماكس ؛ خارج ضوء الشمس: 10000 لوكس ماكس		
الملكية الفكرية الصف	ip42		
نطاقات فك الترميز			
* الأداء النموذجي	نطاقات العمل النموذجية		
	hd نطاق التركيز		
نوع الكود الشريطي	كثافة الرمز	قرب	الآن

رمز 39	مل 5.0	135mm	90mm
من المرجع الأعلى % 100	مل 13.0	8mm	200mm
رمز 39	مل 20.0	8mm	مم 250
قوات الدفاع الشعبي 417	مل 6.8	135mm	مم 95
مصفوفة البيانات	مل 10.0	135mm	مم 110
رمز ريال قطري	مل 20.0	10mm	مم 150
القرار 1 دال الرمز 39	مل 4		
مصفوفة البيانات dالقرار 2	مل 10		
مواد	abs + pc		
بعد	(الماسح الضوئي (70 * 95 * 168 مم) القاعدة (145 * 112 * 747		
الوزن الصافي	(المساحة الضوئية القاعدة 185 ز)		
طلب المعلومات:	ماسح شريطي لاسلكي ثنائي الابعاد بسرعة 433 ميغاهرتز مع مهد 4-W231-اوكيس		
	الماسح الضوئي مع مهد dب: بلوتوث 2-W231-اوكيس		

**ocom**  
All your side

**433MHZ OR BLUETOOTH  
WIRELESS 2D BARCODE SCANNER  
WITH CRADLE**

433MHz

# FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

**1**

**FAST SCAN,HIGH RECOGNITION RATE**



**2**

**STRONG DECODING ABILITY**



**3**

**CRADLE FOR CHARGING AND WIRELESS COMMUNICATION**



**4**

**STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE**



**5**

**NO NEED DRIVER PLUG AND PLAY**





## THE PRODUCT FAMILY

---



## PRODUCT PACKAGING FIGURE

---





## WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT  
INORMATION

---

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),

Together we quest for the best.





## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

**Sales Center:**

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: [www.ocominc.com](http://www.ocominc.com) [www.possolution.com.cn](http://www.possolution.com.cn);

E-mail: [sales15@ocominc.com](mailto:sales15@ocominc.com)

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

*ocominc.com*

*ocominc*