اللاسلكي ماسح الباركود المحمولة مع الذاكرة OCBS-W800 433MHz

مواصفات:

□□□□□□□ □□□□□□□□	
□□□ □□□□:	□□□□ □□□□ □□□□ (VLD) @ 650 □□□□□□□□
□□□□□□□□ □□□□□□ □□□□□□ :	168mm * 72mm 93 *□mm (W * H D *)
□□□□□□□ □□□□□□□□:	130MM * 45MM * 129mm (W * H D *)
□□□□:	ABS + □□□□□□□□□□□ □□□□□ / □□□□□□ □□□□□□□ □□□□
□□□:	370g
□□□□□□ □□□□□ □□□:	□□□□□□□ □□□□□ □□□ .□□□□□.
□□□□□□ □□□:	LED □□□□□□□ □□□□□□
□□□□□:	□□□□□□□ □□□□ □□□ □□□□□□
□□□□□□ □□□□□□□	
□□□□□□ □□□□□ □□□ □□□:	60MM 30mm (□□□□□ □□□□ □□)@ □ 98MM @ 100MM (□□□□□ □□□□ □□)
□□□□□□ □□□□□ □□□□□□□ □□□:	10-450mm (0.25 □□□□□□□ 0.9 □□□□□□□)
□□□□□□ □□□□□ □□□□:	150 □□□□□ / □□□□□□□
□□□ □□□□□:	0.10-0.825mm
□□□□□ □□□□ □□:	1.5 □□□□□)
□□□□□□ □□□□ □□:	UPC / EAN□ UPC / EAN □□□□□□□ □□□ UCC / EAN128□ CODE39□ 39 □□□□□ ASCII □□□□□ Trioptic 128 □□□□□ □128 □□□□□ □39 □□□□□ ASCII □□□□□ Codabar□ 2 □□□□ 93 □□□□□ □5 □□ 2 □□□□□□□ □5 □□□ MSI□ □□□□□□□□□ □11 □□□□□ RSS□ 2 □□□□□□□ 5 □□□ MSI / Plessey□ □□□□□□□ □□□□□□□ / Plessey□ UCC / EAN 128□ □□□□□ □□□□□□□ GS1 DataBar (□□□□□ (□□ □□ □□
□□□□□□:	3.7V / 750mAh□ □□□□ □□□□□□
□□□□□ □□□:	3.0 □□□□□
□□□□□ □□□□□□ □□□□□:	30 □□□□
□□□□:	95mA (25 □(□□□□□MA (□□□□□□□□□□)
□□□□□:	45 :□□□□□ □° 60 :□□□□□□ °
□□□□□ □□□□:	433MHz □
□□□□□□□□□ □□□:	200M (□□□□ □□□)
□□□□□□□□□ □□□□□:	□□ □□ □□
□□□□□□□□ □□□□ □□□□□□□	
□□□□□□□ □□□□:	-10degree □□□□45 □□□□□□□□ □□□□□□□ □□□□□ C (40- □(□□□□□□□degree □□□□□ 60 □□□□□□□□ □□□□□□□degree C (□□□□□□□)
□□□□□□□ □□□□□□□:	5□ -90□ (□□□□□ □□□)
□□□□□□□□□ □□□□□:	1.5 □□□□□ □□□□□M □□□□□□□□ □□□□ □□□□□□□□
□□□□□□□ □□□□□□□:	0 ~ 100000 LUX
□□□□□□□□□ □□□□□□□:	12 ± □□□□□□ □□□□□ □□ □□□□□□KV 6 ± □KV □□□□□ □□□□□□□
□□□□□□□ □□□□□:	CE□ FCC□ □□□□□□□ □2 □□□□□

تفاصيل المنتج:

Product Picture

Features

Simple but not easy
Integrated non-volatile memory
Data transmission distance reaches 200m in open area

Integrated non-volatile memory

Intelligent battery management system, real-time check the remaining battery

www.ocominc.com

All-round show

Parameter

PHYSICAL CHARACTERSTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Width of Scan Field	60mm@30mm（From engine face） 98mm@100mm（from engine face）
Depth of Scan Field	10-450mm（Contrast 0.9 Density 0.25）
Scan Speed	150 scans/sec

Scan Speed	100 scans/sec
Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERSTICS	
Temperature	-10℃ to 45℃ (Operating), -40℃to 60℃ (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

www.ocominc.com

8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

مستندات ذات صلة:

الوقود النووي؟من فضلك انقر هنا ormationهل تريد أن تعرف المزيد من الوقود النووي المشع المنتج.

[مواصفة]

[دليل المستخدم]