مم طابعة الإيصالات الحرارية مع القاطع التلقائي 80

(ألف OCPP-80 :م / ن)

سمات:

- يمكن استخدامه كطابعة قادمة للورق العلوي وطابعة قادمة للورق الأمامي
- هو - هي محول طاقة مدمج ، والذي يتجنب الأسلاك الفوضوية في كل مكان ، مما يوفر مساحة كبيرة
- دعم 8 أنواع تركيبة واجهة وفيرة
- يدعم طباعة الباركود متعدد الأبعاد 1 ورمز الاستجابة السريعة
- دعم وظيفة مراقبة حالة الطابعة
- دعم طباعة بطاقة انتظار وظيفة
- منفذ إيثرنت 100 متر ، نقل بيانات فائق السرعة
- كيلوبايت وذاكرة تخزين عازلة كبيرة تبلغ 256 كيلوبايت NV 256 تخزين شعار
- فاصل ورق قابل للتعديل 48 أو 80 مم للخيار
- كيلو متر رأس الطابعة طويل العمر 150

□□□□□□ □□□□□□□□□:

□□□	
□□□□□	OCPP-80 □□□
□□□	□□□□□□ □□□□ □□ □□ 80 □□□□□□ □□□□ □□□□□□ □□□□□
□□□	□□□□
□□□□□□□□ □□□□□	USB / USB Lan / USB BT / USB WiFi / URL WIFI / URL BT / USB RS232
□□□□□□ □□□□	□ □□□□□□□ □ □□□□ 60-50 □ □□□□ 240- □□□□ 100 □□□□□ □□□□ :□□□□□□□□ □□□□□ 2.5 / □□□□ 24 □□□□□ □□□□
□□□□□□ □□□	□□□□□ 1 / □□□□ 24 □□□□□ □□□□
□□□□□□□□ □□□□□	□□□□□□□□ □□□□□□□ □□□□□ □□□□□ □□□□ □□□□□ □□□□ □□ □□□ □□□□ □□□□ 20 □□□□ □□□))
□□□□□□□ □□□ □□□	150 □□
□□□□□□	□□□□□□□□ □□□□□□
□□□□□	□□□□□ □□□□□□ □□□□□ □□□□□□□ □□□□□ □□□□□□□ □□□□□□ □□□□ □□□□□ □□□ □□□□□□□) □□□)
□□□□□□	□□□□ □□□□ 256 □□□□□□□ □□□□□□ □□□□□□ □ NV □□□□ □□□□ 256 □□□□
□□□□□□□□□□	□□□□ □ □□□□□ □□□ □ □□□ □□□□ □ □□□□ □□□ □ □□□□ □□□□ □ □□□□□□ □□□□ □□□□□□□) □□□ □□□□ □)
□□□□□□□ □□□□ □□□	□□ □□□□□□ iOS / Android / Windows
□□□□□□□ □□□□□□	CE □ FCC □ □□□ □□□□□□□
□□□□□□□ □□□ □□□□□□	
□□□□□□□ □□□□□	□□□□□ □□□□□ □□
□□□□□□□□□	576 □□□□□□ □□ □□□□ 203 □ □□ / □□□□ 8 □□ / □□□□ 512 □□ □□ / □□□□□
□□□□□□□ □□□□	200 □□□□□ / □□ (U / UR) 260 □□□□□ / □□ (UL / U BT / U WIFI) 300 □□□□□ / □□ (URL / URL BT / URL WIFI)

□□□□□□□ □□□	72 □□□
□□□□□□□□ □□□□□	□□□□□□□□ □□□□□□□ □□□□□ □□□□□ □□□□
□□□□□□□ □□□	□□ □□□□□□ ESC /POS
□□□□□□□□ □□□□□□□□	
□□□□□□□□	□□□□□□□ □□□□□ □□□□□ □□□: UPC-A / UPC-E / 13 □□□□□ □EAN13□ / 8 □□□□□ □EAN8□ / CODE39 / ITF / 128 □□□ / 93 □□□ / □□□□□□□ □□□□□□□ □□□□□ □□□□□□□ □□□□□: QR CODE □□□ USB □□ □□□□ UR □□□□ □□□□□□□ □□□□□□□□□ □□□ □□□□□□
□□□□□	□□□□□ GB18030 □□□□□□□□□ / □□□□□□□ □□□□□□□ □□□□□□
□□□□□□□ □□□	384 □□□ □ □□ / □□□□ ANK □ □□□□: A: 12 * 24 3.0 * (□□□) 1.5 □ □□□□ □□ (□□□□□□) FontB: 9 * 17 □□□ (□□□□□□) 2.1 * (□□□) 1.1 □ □□□□ □□□ (□□□□□□) 3.0 * (□□□) 3.0 □ □□□□ 24 * 24 :□□□□□□ / □□□□
□□□□□ / □□□□□□□□□□	□□□□□
□□□□□□□□ □□□ □□ □□□□□ □□□	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 / WestEurope / □□□□□ / □□□□□□ □□□ / □□□□□□□ / □□□□□□□□□ / WPC1252 / PC866 / PC852 / PC858 / IranII / □□□□□□□ / □□□□□□□□ / PT151 □ 1251 / PC737 / WPC / 1257 / ThaiVietnam / PC864 / PC1001 / (□□□□□□□□) / (PC1001) / (PT151 □ 1251) / (WPC1257) / (PC864) / (/ (□□□□□□ □□□□□□□□□□□))
□□□□□	
□□□□□ □□□	□□□□□ □□□ □□□
□□□□□ □□□	48 □□□ 80 / □□□ 76 / □□□ 68 / □□□ 64 / □□□ 56 / □□□ 52 / □□□
□□□□□ □□□□□	0.06 ~ 0.08 □□
□□□□□ □□□ □□□	80 □□□□ □□□ □□□
□□□□□ □□□□	□□□□□
□□□□	
□□□□□	196 * 145 * 135 □□□
□□□	1.65 □□□
□□□□□□ □□□□□	300 * 190 * 180 □□□
12 □□□□□ 1 □□	615 * 370 * 535 □□□ 21.5 / □□□
□□□□	
□□□□□□□□ □□□□□ □□□□□ □□□□	0 □□□□□ □□ □80 ~ □10 □ □□□□□ □□□□ 45 □□□
□□□□□□□ □□□□□ □□□□ □□□□□□□□	-20 □□□□□ □□ □90 ~ □10 □ □□□□□ □□□□ 60 □□□

Mini Receipt Pri
Quick Start Guide

Thermal Receipt Printer
Model: OCPP-80K
Interface:USB&RS232&LAN
Paper Width:80mm
Print Speed:260mm/sec
Power Input:24V/2.5A
Cash Drawer:24V/1A
OCPP80K2137001339
Made in China

Thermal Receipt Printer
Model: OCPP-80K
Interface:USB&RS232&LAN
Paper Width:80mm
Print Speed:260mm/sec
Power Input:24V/2.5A
Cash Drawer:24V/1A
OCPP80K2137100139
Made in China