

OCP-P06: 2016 0000000 0000 0000 IOS 00000 00000 0000 000000 0000

(M / N: OCPP-M06)

000000 000 00 000000 000000 0000 OCPP-M06 00) 00000000 00 IOS + 00000000 00000000 0(00000000
 58 00000000 00000000 0000mm 000000 00000 00000000 000000000 000000000 00000000 000000
 0000 00000 000000 000000000 USB RS-232 .0000 (00000000) 00000000 0000000000 0000000000 000000
 000000 00000 00 0000000000 00000 00000000 000000 00000000 00 00000000 0000 00000000 0000 00 00000
 0000 00 000000000 00000000 000000 8 00 00000000 00000 0000 000000 .(000000 000000 0000 00000000)
 0000000 .000000 CE FCC 00000000000 0000000000 00 00000000.

:

1. Mini .
2. Windows (+ IOS)
3. Bluetooth USB RS232 .
4. SDK
5. 1D 2D
6. Can .
- 7 .One (7) 8
8. Low Lithiumbattery (1500mAh 5 ~ 4) .
9. Powered rechargeablebattery ()
10. Higher 90 mm /
11. 100km
- 12 .Multiple
13. ESC setcompatible / .

□□□□□□:

□□□□□ □□□□□ (W × D × H)	105 × 75 × 45mm □
□□□	134g
□□□□□	□□□□
□□□□□□□ □□□□□	□□□□□□□□ □□ □□□□□□□□
□□□□□□□□ □□□□□	ESC / POS □□□□□□□□ □□□□□□ □□□□□□□
□□□□□□ □□□□□□□□ □□□	48MM
□□□□□□□□ □□□□	90 □□□□□□ □□□mm / □□□□□□
□□□□□	8 203) □□ / □□□□dpi)
□□□□□□ □□□□□	12x24 / 24x24
□□□□□□□ □□□□□	32 16 / □□□□□□□□columns
□□□□□□ □□□	1.5 × 3.0 □□□□□) □□ × H) / 3.0x3.0mm (WXH)
□□□□□□ □□□□□□	58.0 ± 0.1MM 40.0 × □□□mm
□□□□□□ □□□	0.06 0.08 □□□mm □
□□□□□□□ □□□□□□□	□□□□□□□□ □□□□□□ / □□□□□□□□
□□□□□□□ □□□□□□	USB□ RS-232□ □□□□□□□□) □□□□□□□□ □□□□□□□□)
□□□□□	256KB

