OCBS-L006 □□□□□□□ □□□□□□ USB □□□□□□□□ □□□□ □□□□□ □□□□

(M / N: OCBS-L006)

ميزة:

Hمعدل المسح IGH وبعد قراءة طويلة،

ممتازالقدرة د ecode.

KBW، RS232 و USB دعم.

البناء الدائم جنبا إلى جنب مع المستقبل التدقيق.

مواصفة:

خصائص الأداء	
مصدر ضوء:	670-650) مرئي ليزر nm)
معدل المسح:	100 بالاشعة في الثانية
القراءة عن بعد	2.5 ~ 600MM (100٪ UPC / EAN)
نوع الماسح الضوئي:	ثنائية الاتجاه
قرار:	0.10mm (4mil) في PCS 0.9
طباعة على النقيض من الدنيا:	20٪، 650 @) والحد الأدنى يعكس الفرق NM)
فك شفرة القدرة:	UPC / EAN، UPC / EAN مع تكميلية، UCC / EAN128، 39 قانون، 39 قانون ASCII، رمز كامل، شريط خاتمة، معشق 2 من 5، منفصلة 2 من ASCII القانون 128، قانون 128، 39 trioptic، كامل، 5، MSI، 11 قانون، ATA، المتغيرات RSS، 5 من 2 الصينية ... 93، رمز
الخصائص البدنية	
واجهات المعتمدة:	PS2، RS232، USB
الجهد االكهربى:	DC + 5V + 5٪
تيار:	مللي أمبير 100
الخمول الحالية:	العلامة & Itمبير مللي 40 ؛
مصدر الطاقة:	إمدادات الطاقة (RS232) استضافة السلطة أو خارجي
زاوية المسح الضوئي	الميل 45 درجة ارتفاع 60 درجة
الأبعاد:	L165.42mm X W69.72mm X H89.67mm
وزن:	140G (بدون الحامل)
موقف	مع□□□□
اللون:	العاج والأسود
بيئة المستخدم	
درجة حرارة التشغيل:	0 درجة C~ 50 درجة C
درجة حرارة التخزين:	-40 درجة C~ 70 درجة C
رطوبة:	5 ~ دون تكاثف، 95٪ الرطوبة النسبية
التفريغ الكهربائي:	15 تفريغ الهواء -/+ تأكيد ل KV 8 -/+ و KV التفريغ اتصال
إسقاط المواصفات:	1.5 يقاوم M متعددة قطرات لملموسة
آمن:	
EMI / RFI:	CE لجنة الاتصالات الفدرالية الفئة (أ) و
السلامة الليزر:	المنتج 2 الليزر CDRH الفئة

Product Picture

Features

High scan rate and long reading

High scan rate and long reading distance

Excellent decode capability

KBW, RS232 and USB supported

www.ocominc.com

Durable construction combined with future-proofing

All-round show

www.ocominc.com

Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0℃~50℃
Storage Temperature:	-40℃~ 70℃
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.