

11.6 11.6 11.6 11.6 POS 11.6

11.6 11.6 11.6

(M / N: POS -B11.6-W)

11.6:

11.6 Elegant B 11.6 pos.

11.6 intel Celeron 11.6 J1900 2.0 11.6 GH 11.6 11.6 11.6 11.6

2.0 11.6 GHz A83T ARM 8-Core Cortex-A7 11.6 11.6

2 11.6 GB RAM +8GB ROM 11.6 11.6

11.6 11.6 RAM 11.6 2 11.6 + SSG 11.6 11.6 32 11.6 (Windows)

11.6 11.6 11.6 11.6 11.6 11.6 11.6 11.6

11.6 11.6 11.6 11.6 11.6 11.6 11.6

11.6 11.6 11.6 11.6 80 11.6 11.6 58 11.6 11.6

11.6 11.6 11.6 RFID MSR (11.6)

11.6 11.6 11.6

11.6:

11.6 11.6 11.6 11.6 11.6 11.6 11.6 11.6 :11.6

11.6 11.6 11.6 11.6 11.6 11.6 11.6 11.6 :11.6 11.6

11.6 11.6 11.6 11.6 11.6 11.6 11.6 11.6 :11.6

11.6 11.6 11.6 11.6 11.6 11.6 11.6 11.6 :11.6

11.6 11.6:

操作系统 (Windows)	RFID MSR 3 接口 DB25 接口 DB9 RS232 * 3
操作系统 (Android)	3G 4G 接口 LCD VFD 接口 RFID MSR 接口
工作温度	-20 °C 60 °C
尺寸	46 * 43 * 51CM
电源	110-240 60-50 / 50HZ 接口 AC 24 / 12 接口V 接口





POS-B11.6





POS-B11.6





POS-B11.6



[POS -8829](#)

[POS -8912](#)