

15 000000 0000 000000 0000000000

(M/N: 8618-000000 0000)

:

00000000 0000 0 J1900 00000000 2.0 000000 00000000

32 000000 000000 000000 0gb (64 000000 0 (0000000000gbHDD320G 0000000000

00000000 00000000000 0 (00000000) 000000 00000000 000000 0000 0000 5 0

000000 0000 00000000 0000 0 fd 00000000 000 00000000

00000 00000000/00000000 000000 0000 0

00000000:

0000000 00000000 000000 ,00000 ,00000000 00000000 00000 ,000000 00000 :00000000 0

1 00000000 00000000 00 00000000 00000000 00000000 00000000 00000 ,00000 ,00000000 000000 00000 :000000000

1 000000000 00000000 000000 000000 000000 0 00000000 000000 0 00000 000000 0000 0 000000 :000000000

1 000000 00000 ,000000000 00000 ,000000000 ,0000 ,0000000000 00000000 0000000000000000 :0000000000

0000000000:

| | | | |
|---|--|---|--|
| x | | x | |
| x | | x | |

000000:

| | |
|----------------------|----------------------------------------------------|
| 000000 | POS8618 |
| 000 00000000 | 00000 00 00000 |
| 0000 00000000 | VFD220E |
| 0000 000000 | 000000000 0000 0000000 |
| | 000000000 0000 J1900 000000000 2.0 000000 00000000 |
| 000000 | 00000 NM70 |
| 000 000000 | 2 1 * 1066/1333 000000gb (00000000000) |
| 0000 000000 00000000 | 32 00000gb (00000000000) |
| lcd 00000000 0000 | 00000 lcd 00000 15 00000 |
| 00000 | 350 cd/m ² |
| 00000 | 1024 * 768 (00000 0000) |
| 00000000 00000 00000 | 5 00000000 00000000 00000000 00000 00000 |

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 140 : 150 : | |
| 1 * 12 v 1 * 1 * DB9 1 : * DB25 1 * (15) RJ-45 * 1 6 * (2.0) 1 * 1 * 0 °C 40 °C -20 °C 60 °C A/CE /lvm/CCC 410 * 310 * 4 7.6/ AC-DC12/50-60 5/ | |