

PLU 16 16-PORT 16-PORT 16-PORT

(Model: TM-AA-5D)

Overview:

The TM-AA-5D is a 16-port 16-Port 16-Port 16-Port PLU 16. It is designed for high-performance data processing and storage.

It features a robust design and is suitable for industrial environments.

The device is equipped with advanced security features, including a password protection function.

It supports a wide range of protocols and is compatible with various operating systems.

The TM-AA-5D is designed for easy installation and maintenance. It has a compact size and a low power consumption.

It is a reliable and secure solution for your data processing needs.

The device is available in various configurations to meet your specific requirements.

For more information, please contact our sales department.

Specifications:

| | | | | |
|--------------|--|--------|--------|--------|
| Model: | 4000 PLU | | | |
| Ports: | 16-Port 16-Port 16-Port 16-Port PLU: 3-Port 3-Port 3-Port 3-Port 4-Port 4-Port 4-Port 4-Port | | | |
| Dimensions: | 71 | | | |
| Weight: | 22 | | | |
| Power: | 32 | | | |
| Temperature: | 3000 | | | |
| Humidity: | 55 + ~ 10- ° C. 40 + ~ 0 ° C | | | |
| Reliability: | ≤85% RH | | | |
| Input: | AC 220V 50 | | | |
| Output: | LED | | | |
| Security: | 7-Port 5-Port 5-Port 5-Port | | | |
| Resolution: | 30mm 60-MM | | | |
| Resolution: | 75MM / | | | |
| Protocol: | RS232 () () () () | | | |
| Dimensions: | 381 * 428 * 500MM | | | |
| Weight: | 3KG | 6KG | 15KG | 30KG |
| Resolution: | 1G | 2G | 5G | 10G |
| Resolution: | 1/3000 | 1/3000 | 1/3000 | 1/3000 |

| | | | | |
|--------------------|-----|-----|----------|------|
| □□□□□□ □□□□□□ □□□□ | 20G | 40G | 100 □□□□ | 200G |
|--------------------|-----|-----|----------|------|