

USB / RS232 58 mm 0000mm 00000000 00000000 000 0000000

(M / N: OCPP -M06)

0000000 00000 000000000 000000000 0000 OCPP -M06 000) 000000000 00 IOS + 00000000 (000000000 0000000 00 58 00000 0000000000 000000000 00000 00000000 00 000000000 000000000 pos 0000000000 0000 0000 00000 0000000000 USB 0 RS-232 00000 .00000 (0000000000) 00000000000000 00000000000 0000000 0000) 0000000 00000 00 00000 00000 00 0000000 0000000 00000000 000000000 00000000 0000 0000000 0000000 .0000000 0000 00 000000000 00000 0000000 8 00 0000 000000 000000 .(000000000 CE 0 FCC 00000000000 00000000000 00 000000000.

:0000000

- .00000000000 0000000000 0000000 00000 0000 0000 .1
- 2.Windows 0 Java 0 Linux 0 0000000 00000 Android (000 Android + IOS) 0 0000000000 00000000 .3 0 usb 0 rs232 .00000000000 00000000000
- 4. SDK 0 0000000000 00000000000
- 5.1D 0 2 0000000000D (0 00000000000 0000000 0000000 0 (0000000000 00000000000 0000 0 00000000000 0000 00000 00000 0 000000000 00000 0 0000000000 0000 0000000 00000 .6
- 7) 00000 0000000 8 0000 0000 00 00 0000000 0000000 0000000 000000 00000 .7 Android 0 0000000 Apple (00000 0 0000000 000000000 0000 000000000
- 00000 5 ~ 4 0 (0000000 00000 1500) 00000000 00000000 000000000 000000000 000000000 000000000 00000000 .8 0 00000000000
- (0000000 0000000) 0000000 000000 000 0 00000000 000000 0 0000000 0000000 00000000 00 0000000 .9
- 10.Higher 90 0000000000 00000MM / .0000000
- 11.100km .00000000000 0000000000 0000 000000
- .000000000 00000000 00000 .12
- 13. set / 0000000 00 000000000 POS 0

0000000:

000000 0000000 (W × D × H)	105 × 75 × 45mm 0
0000	134g
0000000	000000
000000000 0000000	00000000000 0000000000 000
000000000 0000000	00 0000000000 0000000 000000000 ESC / POS
00000000 0000000000 0000	48MM
000000000 00000	90 0000 0000mm / 0000000
0000000	8 00000 0000 00000 203) 00 / 000000
00000 0000000	12 × 24/24 × 24
00000000 00000	32 00000 16 / 000000
0000000 0000	1.5 × 3.0 0000000000 × 0000000) 00 3.0 × 3.0 / (0000000000 × 0000000) 000
0000000 0000000	58.0 ± 0.1 00 40.0 000000 × 00
0000000 0000	0.06 00 0.08 0000
00000000 00000000	0000000000 0000000 / 000000 0000000
00000000000 0000000	USB 0 RS-232 0 000000000) 000000000
00000	256KB

