□□□□□□□□□ 24 □□□□□ □□□□□□□□□ □□□□□□□ □□□□□□□□□ □□□□
(□□□□□□□: OCBS -W600)

تخصيص:

الخصائص الفيزيائية	
مصدر ضوء:	نانومتر -670 نانومتر 650 @ (VLD) ديود الليزر المرئي
أبعاد الماسح الضوئي:	164 مم * 95 مم * 67 مم(W * H * D)
أبعاد جهاز الاستقبال:	130 مم * 129 مم * 45 مم(W * H * D)
مواد:	سبائك الألومنيوم / ABS + TPR
وزن:	235 جرام
وضع المسح:	محمول باليد؛ وضع المسح ثنائي الاتجاه.
ضوء المؤشر:	الصمام الأحمر والأزرق
صفارة:	حجم الجرس قابل للتعديل
خصائص الأداء	
عرض مجال المسح:	60 □ مم @ 30 مم□من وجه المحرك 98□ مم @ 100 مم□من وجه المحرك
عمق مجال المسح:	2.5-600 0.25 الكثافة 0.9 التباين□مم□
سرعة المسح:	100 عملية مسح / ثانية
دقة المسح:	0.10 ميل 4□مم□ PCS0.9
معدل خطأ البت:	1 / (مليون 5)
القدرة على فك:	UPC / EAN ، UPC / EAN مع الإضافات ، UCC / EAN128 ، Code39 ، Code 39 Full ASCII ، Trioptic Code 39 ، Code 128 ، Code 128 Full ASCII ، Codabar ، Interleaved 2 of 5 ، Discrete 2 of 5 ، الصينية 2 من 5 ، RSS الرمز 11 ، متغيرات ، MSI ، Code 93
البطارية:	3.7 فولت / 750 مللي أمبير ، ليثيوم أيون
وقت الشحن:	3.0 ساعة
وقت الفحص:	30 ساعة
تيار:	100mA (وضع الاستعداد) ؛ 40 مللي أمبير (العمل)
الزوايا:	الملعب: 60 درجة ؛ الإمالة: 45 درجة
مسافة الاتصال:	30 م
تردد العمل:	2.4 جرام
ذاكرة	16 ميغا بايت
واجهة الاتصالات:	يو اس بي
خصائص بيئة المستخدم	
درجة الحرارة:	50درجة مئوية حتى 0 درجة مئوية (التشغيل) ، -40درجة مئويةحتى 70 درجة مئوية (تخزين)
الرطوبة النسبية:	5٪ -90٪ (دون تكاثف)
مواصفات الإسقاط:	يتحمل 1.5 متر قطرات متكررة على سطح الخرسانة
الإضاءة المحيطة:	0 ~ 100،000 لوكس
التفريغ الكهربائي:	من التفريغ الاتصال KVتفريغ الهواء و ±6 KVيتوافق مع ±12
شهادة سلامة:	CE ، FCC ، الفئة 2 ، RoHS

تفاصيل المنتج:

Product Picture

www.ocominc.com

BATTERY PACK
FOR BAT-8019

Features

Simple but not easy
2.4 G wireless laser barcode scanner
Scan Speed:100scans/sec

Data transmission distance reaches 30m in open area;

Scan Time:30hours

All-round show

Parameter

PHYSICAL CHARACTERSTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Width of Scan Field	60mm@30mm（From engine face） 98mm@100mm（from engine face）
Depth of Scan Field	2.5-600mm（Contrast 0.9 Density 0.25）
Scan Speed	100 scans/sec
Scan Precision	0.10mm（4mil） PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB,RS232,PS2
USER ENVIRONMENT CHARACTERSTICS	
Temperature	0℃ to 50℃ (Operating), -40℃to 70℃ (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

المستندات ذات الصلة:

هل تريد معرفة المزيد من المعلومات عن المنتج الرجاء الضغط هنا.

تخصيص