

## 2 2D Barcode D 433 200MHz USB (OCBS-W230)

Dimensions		95x65x155mm	
Material		ABS + PC	
Capacity		160G	
Resolution		617 dpi	
Resolution		625 dpi	
Temperature Range		39 ° (H) × 25 ° (V)	
Rotation		0-360 °	
Accuracy		± 65 μm	
Accuracy		± 60 μm	
Accuracy		25 μm	
1D	UPC / EAN, UPC / EAN Bookland, EAN, ISSN, UCC, CODE128, GS1-128, ISBT 128, 39, FullASCII, Trioptic 93, 32, 39, Code11, 5 2, 5 2, 2 of 5, Codabar, MSI, 5 2, DataBar variants, GS1, 5 3, ISBT CONCAT		
2D	PDF417, MicroPDF417, TLC-39, Maxicode, MicroQR		
Interface		USB	
Resolution		100 :dots/mm, 300 :dots/mm (dots)	
Operating Temp		-10 °C - 45 °C	
Storage Temp		-20 °C - 65 °C	
Humidity		5% - 85%	
Humidity		5% - 95%	
Power		1.8 W, 300mA	
Power		DC 5V, 350mA	
LUMINATION		3.000 :dots/mm, LUX 86000 :dots/mm, LUX	
EMC		EN50081, par1	
FCC		EN50082, par1	
IP		IP42	
Barcode DECODE			
Barcode		HD Barcode	
BAR CODE	Resolution	Resolution	Resolution
39	5.0	5MM	90 mm
100 UPCA	13.0	8MM	200MM
39	20.0	8MM	250MM
PDF 417	6.8	5MM	95MM
	10.0	5MM	110MM
	20.0	10MM	150MM
1 D 39		2.8 0.071	(mm)
2 D		4.8 0.122	(mm)



