

# 10寸POS终端windows

(M/N:POS-B10/B10-A)

□□:

□□□□□□□□J1900 □□ 2.0GHz cpu, windows □□□□  
 2.0GHz A83TARM 8-□ Cortex-A7 □□□,android □□□□  
 2GB RAM+8GBrom □□ (□□)  
 2GB RAM+32GBssd □□ (Windows)  
 □□□□□□□□  
 □□□58mm □80mm □□□□(□□)  
 □□□MSR / rfid □□□(□□)  
 □□□□□□

□□□□:

□□□□: □□, □□,□□□□, □□ □□,□□□□□□□□□□  
 □□□□: □□□□, □□□□,□□□□□□, □□□□□□□□□□□□  
 □□: □□□□, □□□□□□,□□□□, □□□□□□□□□□□□  
 □□: □□□□□□□□□□□□, □□,□□, □□, □□□□□□

□□□□:



□□:

□□	pos-b10/pos-b10-a
□□①	□□□ □□ J1900□□□□ □□2.0GHz (windows)
□□②	2.0GHz A83T ARM 8-□ Cortex-A7 □□□ ( □□)
os①	Windows7 (Beta)
os②	android 5.1
□□①	2GB ram 32GB □□□□ (windows)
□□②	2GB ram 8GB rom (android)
□□ □□	□□□□□□□□
□□ □□	□□10.1 □, □□10.1inch
□□	□ □ □
□□□	58mm □□□□□□□□□□□□□□□□80mm □□□□ (□□)
i/o □□ (①J1900)	usb*4
	rj45*1
	rj11*1
	hdmi * 1 (□□ □□□)
	DB9 RS232 □ * 1
i/o □□ (②A83T)	rj11*1
	tf □□ * 1
	rj45*1
	hdmi * 1 (□□□□□)
	usb*2
	DB9 RS232 port*1
	audio*1
usb otg □□	
□□□□ □□	0°C□40°C

□□□□ (□□)	□□, wifi, gps
□□ (Widows)	□□□□, rfid, msr, □□,3G, DB25 □□□□, DB9 RS232 port*3 □□□□□□
□□ (□□)	3G, □□, lcd □□□□, rfid, msr, □□□□□□
□□ □□	-20°C to 60°C
□□□□	46 * 43 * 51 □□
□□ □□□	110-240v/50-60hz □□□□, □□ dc12/5a □□