

OCBP -M1001 4

M / N OCBP -M1001



- 1.
- 2. pos
- 3.
- 4. LCD im
- 5.
- 6.

	80mm / s
	70mm / s
	8 / mm
	100mm / 72mm / 48mm / 37.5mm
	ASCII GB18030 BIG5
	A 12 * 24; B 8 * 16
	40
	13
	0.06~0.16 mm
TPH	50
	1D EAN-13 EAN-8 UPC-A UPC-E CODE39 CODE93 CODE128 CODABAR INTERLEAVED 25
	2D PDF417 QR CODE DATA
	CPCL / ESC- POS
	Windows 98 / ME / 2000 / NT / XP / 2003 Server / Vista / Win7 / Win 8 / Win10

接口	USB / 耳机
芯片	瑞芯微 RK3288
内存	DDR3 1GB
存储	闪存 512 kb; RAM 128kb
分辨率	32K
SDK	Windows CE; Windows Mobile 5.0 / 6.0; Symbian; 安卓 Android
摄像头	460 万像素
充电器	DC9V / 2A
电池	锂离子电池 7.4 V / 2300 mAg
重量	100 克
厚度	约 3 毫米
尺寸	360 毫米
功耗	500 毫瓦
接口尺寸 x 接口	140 毫米 x 115 毫米 x 51 毫米
温度	0 度
湿度	-10-50 °C
压力	10 - 80 帕
其他	支持多种传感器和接口
其他	支持 USB 接口 CD 接口
	支持多种接口



OCBP-M1001









□□□□□□□□



□□

► Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant

