

12 pos (M / N POS-B12 / B12-A)

Spec

CPU 1900 2.0GHz
 Android 2.0GHz A83T ARM 8 Cortex-A7
 2GB RAM + 8GB ROM Android
 2GB RAM + 32GB SSD Windows
 58mm 80mm
 MSR RFID
 12V

Option

12V
 12V
 12V
 12V

Accessories



Table

Model	POS-B12 / POS-B12-A
Board①	CPU 1900 2.0GHz
Board②	2.0GHz A83T ARM 8 Cortex-A7
OS①	Windows 7
OS②	Android 5.1
Memory①	2GB RAM + 32GB SSD Windows
Memory②	2GB RAM + 8GB ROM Android
Case	58mm 80mm
Weight	1200g
Power	12V
Dimensions	58mm 80mm
I/O ① 1900	USB * 4 RJ45 * 1 RJ11 * 1 VGA * 1 HDMI * 1 DB9 RS232 * 1
I/O ② A83T	RJ11 * 1 (Optional) TF * 1 RJ45 * 1 HDMI * 1 USB * 2 DB9 RS232 * 1 IR * 1 USB OTG * 1
Operating Temp	0°C ~ 40°C
OS Android	WiFi
Accessories ①	LCD VFD RFID MSR 3G DB25 DB9 RS232 * 3
Accessories ②	3G 4G LCD VFD RFID MSR
Storage Temp	-20°C ~ 60°C
Power Input	46 * 43 * 51mm
Power Output	110-240V / 50-60HZ 12 / 24V

pos□□□□pos□□□□pos□□