

15" Android Pos

POS -15T01-W / A



□□□

| □□□□□□

| 15.6" 1366 * 768 □□□□□□

| 360 □□□□□□

| □□ Windows □ Android □□

| □□□□□□□

| □□□□ 15.6" □□ 11.6" □□□□□□

| MSR □□□□□□□

| □□□□□□□□□□□□□□□□

□□□□□

| □□□□□□□□□□□□□□□□□□□□□□□□

| □□□□□□□□□□□□□□□□□□□□□□□□

| □□□□□□□□□□□□□□□□□□□□□□□□

| □□□□□□□□□□□□□□□□□□□□□□□□

□□□

□□	POS -15T01-W / A□□□□Windows□W□□□□Android□A□
□□①	Windows□□□1.99 GHz J1900N
□□②	□□1.8GHz RK3288□Android□□
Windows□□□□	Windows 7 Ultimate□□□□□□□□
□□□□□□	Android 6.0
Windows RAM	4GB□□2GB 8GB□□
Android RAM	4GB
Windows □□	64GB SSD□□□□□128GB
Android □□	8GB eMMC□□□32GB TF□□□
□□□□	15.6□□□□□□
□□□□	15.6□□□11.6□□
□□□□□□	VFD□LCD
□□□□	1366 * 768
□□□□	□□□□□□□□
□□	350cd /m ²
□□	□□□□150;□□□□140
J1900 I / O□□	VGA * 1□USB * 5□RS232 * 1□DC□□* 1 RJ45□□□□□□□□* 1□□□□□□* 1
RK3288 I / O□□	USB * 5□RS232 * 2□DC□□* 1□RJ11□□□□□□□□* 1 RJ45□□□□□□□□* 1□□□□□□□□* 1□MIC * 1
□□□□□□	0□40□□□□
□□□□□□	-20□60□□□□
□□□□□□	110-240V / 50-60HZ□□□□□□□□DC12 / 5A□□



POS-15T01





POS-15T01







POS-15T01



02 Equicom ...

OCOM " " OEM / ODM

▶ Company



▶ Certificates



▶ Payment



□□□□□□□□

· POS□□□□□□□□□□□□□□□□□□

· □□□□□□500□□□□□□□□

· 1□□□□□□□□□□□□02□Star ...

· □□163□□□/□□□2600□□□□□□

· □□□□□□□□□□24□□□□□□□□

· □□12□OEM / ODM□□□□□□□□□□

· □□□□□□□□□□□□□□□□

· □□ISO 9001□FCC□CE□Rohs□Soncap□SASO□POA□BIS□□□□□□□□

· □□□□□□□□□□□□□□□□□□□□□□

· □□□□□□□□12 + 1□□□□□□□□□□□□

· □□“□□□□□□”

· □□“□□□□□□□□□□□□□□□□”□□□□□□



