

15.6 Windows POS

POS -15T01-W / A

□□□

□□□□□□□□

15.6□□1366 * 768□□□□□□□□;

360□□□□□□□□

□□Windows□Android□□□

□□□□□□□□

□□□□□15.6□□□11.6□□□□□□□□

MSR□□□□□□□□

□□□□□□□□□□□□□□□□□□

□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□

□□	POS -15T01-W / A□□□□Windows□W□□□□Android□A□
□□①	Windows□□□1.99 GHz J1900N
□□②	□□1.8GHz RK3288□□□Android□□
Windows□□□□	Windows 7 Ultimate□□□□□□□□
□□□□□□	Android 6.0
Windows RAM	2GB□□4GB 8GB□□
Android RAM	2GB
Windows□□□	□□32GB SSD□64GB□128GB
Android□□□	8GB eMMC□□□32GB TF□□□
□□□□	15.6□□□□□
□□□□	15.6□□□11.6□□
□□□□	VFD□LCD
□□□	1366 * 768
□□□	□□□□□□□□

亮度	350cd / m ²
尺寸	1500mm*1400mm
J1900 I / O	VGA * 1 USB * 5 RS232 * 1 DC * 1 RJ45 * 1 * 1
RK3288 I / O	USB * 5 RS232 * 2 DC * 1 RJ11 * 1 RJ45 * 1 * 1 MIC * 1
重量	0.4kg
温度	-20~60℃
电源	110-240V / 50-60HZ DC12 / 5A



POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01



