

15.6 POS

POS- 1516)

OCOM POS Android/Window MSR or VFD

POS

- l. 15.6
- m.
- n.
- o.
- p.
- q.
- r.
- s.
- t. MSR

POS

POS-15 16	POS-15 16-A
15.6 Windows POS	15.6 pos
ABS	
Display	
15.6	
1366*768 1920*1080	
30 Ocd/2	
1 60 : 1 50	
GG	
15.6 W W/o 1366*768 1920*1080	
2*20 VFD 2*20 LCD	
Bay Trail J1900 2.0GHz intel core I3 / I5 4GB CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB	2GB DDRIII 4GB
Msata SSD 64GB 256GB	8GB eMMC 32GB TF
ALC662 ALC5640	Real Tek ALC5640
10/100Mbs, Realtek RTL8111F Mini PCI-E WIFI	10M/100M RTL8201F, 10M/100M/1000M RTL8211E
Windows 2010 7 8 WEPOS, Linux	7.1 Android 8.1
power*1	
12V DC *1	
RJ-45*1	
USB * 4	
(RS232) * 1	(RS232) * 2
VGA(15Pin D-sub)*1	RJ11 *1
*1	M in *1, *1
J 4.0 5.0	

□□□□□□□□	460*185*420 mm □□□□
□□	
□□□□	0 □ 40 □□□
□□□□	- 1 0 □ 60 □□□
□□□□	10%~80% □□□
□□□□	10%~90% □□□
□□	
□□□□□□	110-240V/50-60HZ□□□□ i □□ , DC12 V /5A □□□□□
□□□□	□□□□/□□/□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□
□□	
□□	FCC A □□/CE □□/□□/□□/□□/□□









