

# QR

## OCBS-2008

### QR

- QR
- QR
- QR
- 4mil
- QR
- SDK / API
- QR
- QR

### QR

QR		LED
QR		
QR		
QR		LED
QR		
QR		CMOS
QR		640 * 480 256
QR		13mil UPC40
QR		50; 20
QR		≥4mil
QR	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, EAN, Bookland, ISSN, 39, 39, ASCII, 32, Trioptic, 39, 5, 2, 5, 5, NW7, 128, UCC / EAN 128, GS1-128, ISBT 128, CODE93, 11, USD-8, MSI / Plessey
QR	2D	PDF417, MicroPDF417, QR, DataMatrix, Aztec, GS1
QR		39, 5mil, 50, 120, 39, 10MIL, 25, 250, UPC / EAN, 13mil, 20, 320, 7.5mil, 63, 150, PDF417, 6.6mil, 62, 145
QR		±45° @ 0°, ±30° @ 0°, ±45° @ 0°
QR		
QR		USB, USB COM
QR		3.3V, 5V DC
QR		2.0, 400
QR		2.5, 450
DC		5.5V 1A
LED		I
EMC		FCC 15, IEC60825-1, EN55022 B
QR		
QR		-20, +60°C, -4, 144
QR		-30, +70°C, -22, 158
QR		5 - 95
QR		1.5, 5.0
IP		IP54
QR		
QR		
QR		156 * 68 * 83
QR		195
QR		48 * 36 * 47CM, 20, 13.5
QR		48 * 39 * 52CM, 30PCS, 15KG



