

1D 2.4G

Appearance;
 100mm/; ;
 ;
 ;
 ;

OCBS -W011-B

Wavelength	650-670nm
Power	100mW
Beam Diameter	2.5~600mm 100 UPC / EAN
Beam Quality	M2
Spot Size	PCS 0.9 0.10mm 4mil
Resolution	30 lines/mm @ 650nm
Barcode	UPC / EAN, UPC / EAN, UCC / EAN, 128, 39, 39, ASCII, 39 trioptic, 128, 128, ASCII, codabar, 2 of 5, 2 of 5, 93, MSI, 11, ATA, RSS, 2 of 5
Frequency	433MHz, 433MHz, usb, USB
Modulation	433M hz, 300, 15
Battery	900mAh, 3.3V
Weight	100g
Current	< 40mA
Interface	USB
Viewing Angle	45°, 60°
Dimensions	L165mm X W63mm X H87mm
Barcode	129
Material	ABS
Color	Black
Temperature	0~40°C
Storage Temperature	-40~60°C
Humidity	5~95%
Electrostatic Discharge	+/- 15KV, +/- 8KV
Shock	1.5ms
EMI / RFI	FCC A, CE
Regulatory	CDRH 2

OCBS -W011-B

OCBS-W011 100mm/; ;

