

2 USB OCBP-006

OCBP-006

□□□

1.Support □□□□/□□□□

2.□□□□□□□□

3.□□□□□□□□□□

4.□□□□□□□□

5.Modular □□□□□□□□□□□□□□□□

□□□

□□ □□	□□ □
□□ □□	203DPI
□□ □□	20-60mm□
□□ □□	MAX□127□□□□; MIN□50.8□□□
□□ □□	DRAM□4M FLASH□4M
□□ □□□□	□□□□□□
□□ □□□□	□□□□□□
□□ □□□□	USB
□□ □□□□	□□□□□□
□□ □□	CODE128□EAN128□ITF□CODE39□CODE93□EAN13□EAN13+2□EAN13+5□EAN8□EAN8+2□EAN8+5□CODABAR□POSTNET□UPC-A□UPCA+2□UPCA+5□UPC-E□UPCE+2□UPC-E+5□POST□MSI□MSIC□PLESSEY□ITF14□EAN14□ORCode□IDM□PDF417
□□ □□	FONT 0□FONT 8
□□□□□□□□	□0°□90°□270°□360°□□□□□□□□□□1□10□; 0°□90°□270°□360°□□
□□ □□	□PCX□BMP□□□□□□□□FLASH□DRAM
□□ □□	□□□□□□□□□□ □□□
□□ □□	20□□□60□□
□□ □□	MAX80□
□□ □□	MIN25□
□□ □□	□□
□□ □□	DC12V□ 3A
□□ □□	1.04KG
□□ □□	190□□□×135□□□×137□□□mm
□□ □□	5□45°C□20-80□RH□□□□□□
□□ □□	40□55°C□≤93□RH□40°C□
□□ □□	□□