

## 2

OCBP-M18

;

Android App;

bartender;

;

;

50mm;

;

/ /

Android iOS;

2600mAh 7.4V 14.8Wh;

5 7;

90 /

ESC / POS JPL TSPL CPCL 4;

360;

IP54

|  |                       |
|--|-----------------------|
|  |                       |
|  | ESC / POS TSPL JPL    |
|  | = 48 384              |
|  | 90 /                  |
|  | 8 / mm 203dpi         |
|  | 57.5 ± 0.5mm x 50.0mm |
|  | 0.06 0.12mm           |

|        |                                    |
|--------|------------------------------------|
| □□□    | □□□□/□□                            |
| □□     | USB□□□                             |
| □      | 256KB                              |
| □□□□□  | 9V DC / 1A                         |
| □□□□   | 4-5□□□                             |
| □□□□   | 2600mAh□7.4V 14.8Wh                |
| □□□□   | □□5□□□□□□□□7□                      |
| □□□□□□ | 50KM                               |
| □□□□   | □□□□□□□□□□                         |
| □□□□   | □□□-10~50°C□□□□10□~90□             |
| □□□□   | □□□-20~70°C□□□□5□~95□              |
| □□□□   | □□□□□□□□□□□□□□30□ASCII□□□□         |
| □□     | □□□□□□□□“1234”□□□□□□□□□□□□□□□□6□□□ |
| □□     | □□□0.4kg /□□□□□□0.7kg /□           |
| □□□□   | 13.5 * 13.5 *11□□                  |



# OCBP-M18





OCBP-M18





# OCBP-M18



[OCBP -M18 SDK](#)

[OCOM](#)