

2pos

OCPP - M07

□□

- ñ □□□□□□□□□□;
- ñ □□Windows□Java□Linux□Android□IOS□□□□;
- ñ □□□□USB□RS232□□;
- ñ □□□Android□IOS□WIN CE□SDK;
- ñ □□1D□2D□□□□QR□□□□□□□;
- ñ □□□□□□□□□□□□□□□□;
- ñ 57 * 50□□
- ñ □□□□□□□□□□8□□□□□□□7□Android□□□Apple□□□□□□□□;
- ñ □□□□□□□□□□1500mAh□□□4~5□;
- ñ □□ □□□□□□ □□□□□□□□□□□□□□□□;
- ñ □□□□□□□□90□□/□;
- ñ 100□□ □□□□□□□□;
- ñ □□□□□□;
- ñ ESC / POS□□□□□□;

□□□

□□□□□×□×□□	105×75×45□□
□□	134□
□□	□□
□□□□	□□□□
□□□□	ESC / POS□□□□□□
□□□□□□□□	48□□
□□□□	□□90□□/□
□□□	8□/ mm□203dpi□
□□□□	12x24 / 24x24
□□□	32□/ 16□
□□□□	1.5 x 3.0 mm□□x□□/3.0x3.0mm□□x□□
□□□□	58.0±0.1mm x□□40.0mm
□□□□	0.06□0.08□□
□□□	□□□□/□□□□
□□	USB□RS-232□□□□□□□□
□	256KB
□□□□□□	9V DC / 2A
□□□□	7.4V DC / 1500mAh;□□□□□□4-5□□□□□□□□□□□□□□□120-150□□□□
□□□□	□□□□□□□□□□
□□□□	□□□-10~50°C□□□□□10□□90□
□□□□	□□□-20~70°C□□□□□5□□95□
□□□□	□□□□□□□□□□□□□□30□ASCII□□□□
□□	□□□□□□□□“1234”□□□□□□□□□□□□□□□□6□□□

□□□□□		3.5 *1.1□□
□□□□	OCPP -M07-BB	Android□USB + COM +□□□□□
	OCPP -M07-BB-AI	Android + IOS□USB + COM +□□□□□
	OCPP -M07-B	Android□USB + COM +□□□□□□;
	OCPP -M07-U	□□□□□Android□USB + COM□□□□□□
	OCPP -M07-BB-AA	Android + IOS□USB + COM +□□□□□□□□7□android + 1□□□□





OCPP-M07



• 500...

• 12 + 1 ... 24

• 30 ... DOA ... DOA

• ...

4. ...

• T / T, LC, Western Union, Escrow, T / T, Paypal, Moneybookers, Visa, MasterCard, Maestro, Solo, Carte Bleue, PostePay, CartaSi, 4B, Euro6000

5. ...

• ...

6. ...

• Eruopean ...

• 159 ... 2200 ... 02 ... 500 ... 50

OCOM

- 500 ... POS, Auto-ID
- ... 02, Star
- 2200 ... 159
- 11 ... OEM / ODM
- POS
-
- ISO, FCC, CE, Soncap, POA, BIS
- 12 + 1
- " "
- ...