

2.4G USB 1D

M / N OCBS -W0600

Table

Table	
Light Source	VLD @ 650 nm-670nm
Dimensions	164mm * 67mm * 95mm W * H * D
Dimensions	130mm * 45mm * 129mm W * H * D
Material	ABS + TPR /
Weight	235g
Color	Black; Silver
Light Type	LED
Light Color	Red
Table	
Operating Time	60min @ 30% 98min @ 100%
Beam Diameter	2.5-600mm @ 0.9-0.25
Beam Diameter	100mm
Beam Diameter	0.10mm 4MIL PCS0.9
Beam Diameter	1 / 500
Barcode	UPC / EAN UPC / EAN UCC / EAN128 Code39 Code 39 ASCII Trioptic Code 39 Code 128 Code 128 Full ASCII Codabar Interleaved 2 of 5 Discrete 2 of 5 Code 93 MSI 11 RSS 2 of 5
Battery	3.7V / 750mAh
Current	3.0A
Current	30A
Current	100mA; 40
Angle	60°; 45°
Angle	30
Frequency	2.4G
Interface	USB
Table	
Temperature	0°C. 50°C. -40°C. 70°C.
Humidity	5%-90%
Power	1.5
Light Intensity	0~100,000 LUX
Voltage	±12KV ±6KV
Compliance	CE FCC Class 2 RoHS

Table



Wireless Barcode Scanner

OCBS-W600



Product Picture





Features

Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100scans/sec



Scan speed: 10000/second

Data transmission distance reaches 30m in open area;



Scan Time: 30hours

