

2015

□□□□

2015□□□□□□□□□□□□□□

□□□□□□;

□□3□□□□□□210□□75BPI;

USB□□□□□;

□□□□□□500,000□□□□□;

□□□□□□ISO7811 / 7812□ANSI□AAMVA□CA DMV□□;

□□□□□

□□	90□□□L□×26□□□W□×28□□□H□		
□□	85□□□□		
□□	+ 5V□DV±5□		
□□□	40□□□□□□		
□□□□	□□□□		
□□□	ISO7811 / 7812		
□□□□	ISO 1□IATA□	ISO 2□ABA□	ISO 3□MINTS□
□□□□	210 BPI	75 BPI	210 BPI
□□□□	79□□□□7□	40□□□□5bits□	107□□5bits□
□□	USB /□□		
□□□	□□0.76±0.08□□		
□□□	□□1.5□□□□		
□□□□	10□150□□/□		
□□□	500000□□□□□1□□□□□□		
□□□	□□0.5□□SE□□□□		
□□	□□□-30°C□+ 70°C□□□-20°C□+ 70°C		
□□	□□□0□□95□RH□□□20□□90□RH		

□□□□□□□



□□□□□

□□□□□□□□□□□□ □□□□□□

□□
□□□□
SDK