

260mm/3 pos (OCPP-80G)

pos

- 1.Desktop
- 2.Supports 1D QR
- 3.100M, 2M
- 4.Supports 256KB 2M
- 5.Supports OPOS
- 6.Supports 260 mm/
- 7.3

pos

mm:	mm
mm:	230mm/ 260mm/
mm:	79.5±0.5mm
mm:	Φ80mm
mm:	0.06-0.08 mm
mm:	576/line512 /
mm :	3.75mm
mm:	ESC/POS
mm:	Serial+USB+Lan/36P port/25P + USB/
c mm:	1million
print2009 mm:	100
mm :	2048Kbytes
mm:	256Kbytes
mm:	AC110V/240V50 ~ 60
mm:	DC 24 v/2.5A
mm:	DC 24 v/1 a
mm:	(0~45) (10~80%)n-
mm:	(0-45) (10-80%)n-
mm:	(-10~60°C);humidity (10~90%)
mm:	FontA: 1.5 * 3.0mm/FontB1.1 * 2.1mm
mm:	upc-E/JA/EAN13/JAN8/EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 ( )
mm:	PC347PC850PC860PC863PC865 WPC1252PC866Cyrillic#2PC852Latin2 PC858IranIIPT1511251
mm:	mm: 1.25Kg; mm: 190×145×143mm ( * * )

pos





[www.ocominc.com](http://www.ocominc.com)





[www.ocominc.com](http://www.ocominc.com)





□□□□:

\*□□

\*IP □□□□□□

\*□□□

\* □□ windows □□□□□□

\*Linux □□□□

\*□□□□□□□□

\*cd □□