

20000000433MHz0000

(OCBS-W230)

0000	
0000	95x65x155mm
00	ABS+PC
00	160g

0000			
0000	617 nm LED		
0000	625 nm LED		
0000	39° (H) x 25° (V)		
000	0 - 360°		
00	± 65°		
00	± 60°		
000000	00025%		
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 FullASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 DataBarvariants, Korean 3 of 5, ISBT Concat		
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec		
00	USB00		
0000	0010000030000Max0		
0000	-10° - 45°C		
0000	-20°C - 65°C		
0000	5%-85%		
0000	5%-95%		
000	00001.8m00000000000		
0000	DC 5V0350mA		
000	003.000 LUX max00000086000LUX max		
EMC	EN50081, par1 standard		
FCC	EN50082, par1 standard		
0000	IP42		
0000 DECODE RANGES			
Typical Performance*	0	Typical Working Ranges	0
0	0	HD Focus Range	0
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	0	2.8 mil (0.071mm)	0
Resolution 2D Data Matrix	0	4.8 mil (0.122mm)	0