

2D POS □□□□□□□□□□□□□□
 (□□: **OCBS T201**)

□□□□:

□□□□□□□□□□□□;
 □□□□□□□□□□□□;
 □□□□□□□□□□□□;
 □□□□□□□□□□□□□□;
 □□□□□□□□□□□□

□□□□:

□□□□	
□□	□□ LED
□□□□	□□□□□□
□	□□
□□□□	KBW□RS232□USB
□□□□	
□ (Lx W x H)	□□□□ 78 □□ x 75 □□ x 141 □□ (3.2" x 3.3" x 5.9")□
□□	□□ size180 g (12 □□)
□□□□	
□□□□□□	5.5 VDC ± 0.25 V
□□□□	2.0 W (430 □ @ 5 V)
□□□□	0.5 W (100 □ @ 5 V)
□□□□	
□□□□	0 ° C-40 ° C
□□□□	-40 ° C-60 ° C
□□	0%□ 95%□□□□ (□□□)
□□□□	□□□ 1.5 □□□□□□□□□□
□□	□□□□□□□□□□□□□□
□□□□	
□□□□	□□□ (640 X 480)
□□□□	□□□□□□□□□□ 20%
□□□□	70 °□75 °

□□□□□:

×

×

×

×

×

×

×