

2D

-W230

□□□

□□□□	617□□LED		
□□□□	625□□LED		
□□□□	39°□H□×25°□V□		
□□□□	0 - 360°		
□□	±65°		
□□	±60°		
□□□□□□	□□25□		
1D	UPC / EAN□□UPC / EAN□□□□BooklandEAN□□ISSN□UCC□□□□□□□□Code128□GS1-128□ISBT 128 □□39□□39□□ASCII□□Trioptic 39□□32□□93□□Code11□□□□□□2 5□□□2 5□□□2of 5□□□□□□□□5□□2□GS1 □□Barvariants□□□3 5□□□□□□□Concat□		
2D	PDF417□MicroPDF417□□□□□□TLC-39□□□□□□MAXICODE□QR□□MicroQR□□□□□□		
□□	USB		
□□□□	□□□1□□□□□□□□□300m□□□□□□		
□□□□	-10□□□ - 45□□□		
□□□□	-20□□□ - 65□□□		
□□□□	5□-85□		
□□□□	5□-95□		
□□□	□□□□□1.8□□□□□□□□□		
□□□□	DC 5V□350mA		
Lumination	□□□3.000 LUX□□;□□□□□□□86000LUX□□		
EMC	EN50081□PAR1□□		
FCC	EN50082□PAR1□□		
IP□□	IP42		
□□□□			
□□□□*	□□□□□□□□		
	HD□□□□□		
□□□□	□□□□	□	□
39□	5.0□	5□□	90□□
100□UPCA	13.0□	8□□	200□□
39□	20.0□	8□□	250□□
PDF 417	6.8□	5□□	95□□
□□□□	10.0□	5□□	110□□
□□□	20.0□	10□□	150□□
□□□1D□39	2.8□□□0.071□□□□		
□□□□□□□□□	4.8□□□0.122□□□□		
□□	ABS + PC		
□□	95x65x155mm		
□□	160□		
□□□□□	18.2X11.7X11.2cm		
□□□□□	374□		

