

## 2d □□□□□□□□ (OCBS-W230)

□□□□□□300□□□□100□  
 □□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□  
 □□□5□□□□□□  
 □□□□□□□□□□□□

□□□□	95x65x155mm
□□	ABS+PC
□□	160g

□□□□	617 nm LED
□□□□	625 nm LED
□□□□	39° (H) x 25° (V)
□□□	0 - 360°
□□	± 65°
□□	± 60°
□□□□□	□□□25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 FullASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 DataBarvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
□□	USB□□
□□□□	□□100□□□□300□□Max□
□□□□	-10° - 45°C
□□□□	-20°C - 65°C
□□□□	5%-85%
□□□□	5%-95%
□□□	□□□□1.8m□□□□□□□□□□
□□□□	DC 5V□350mA
□□□	□□3.000 LUX max□□□□□□86000LUX max
EMC	EN50081, par1 standard
FCC	EN50082, par1 standard
□□□□	IP42

□□□□ DECODE RANGES			
□□□□	□	□□□□	□
□	□	□□□□	□
□□□□	□□□□	□	□
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	□	2.8 mil (0.071mm)	□
Resolution 2D Data Matrix	□	4.8 mil (0.122mm)	□



